

```

<IfModule env_module>
# No GZIP for script-based file downloads.
  SetEnv no-gzip 1
</IfModule>

<IfModule rewrite_module>
# Enable symlinks (required for rewrites).
  Options +FollowSymLinks

# Enable rewrite and configure base.
  RewriteEngine On
  RewriteBase /

# Initialize all environment variables we're using below.
  RewriteCond %{ENV:s2member_file_download_setup} !^complete$
  RewriteRule ^(.*)$ -
[E=s2member_file_download_wp_vdir: 0,E=s2member_file_download: $1,E=s2member_file_stream: 0,E=:

# Handle virtual directories, common on multisite networks.
  RewriteCond %{ENV:s2member_file_download_wp_vdir_check} !^complete$
  RewriteCond %{THE_REQUEST} ^(?: GET| HEAD)(?: [\ ]+)(?: /)([_0-9a-zA-Z-]+/)(?: wp-content/)
  RewriteRule ^(.*)$ - [E=s2member_file_download_wp_vdir: ,E=s2member_file_download_wp_vdir: 1

# Handle streaming download requests via the rewrite engine.
  RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-stream/)(.+)
  RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%2,E=s2member

  RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-stream-(.+)/)(.+)
  RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%3,E=s2member

# Handle inline file requests via the rewrite engine.
  RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-inline/)(.+)
  RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%2,E=s2member

  RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-inline-(.+)/)(.+)
  RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%3,E=s2member

# Handle storage specifications via the rewrite engine.
  RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-storage-(.+)/)(.+)
  RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%3,E=s2member

```

*# Handle remote authorization requests via the rewrite engine.*

```
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-remote/)(.+)$  
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%2,E=s2member
```

```
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-remote-(.+)/)(.+)$  
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%3,E=s2member
```

*# Handle SSL file requests via the rewrite engine.*

```
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-ssl/)(.+)$  
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%2,E=s2member
```

```
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-ssl-(.+)/)(.+)$  
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%3,E=s2member
```

*# Handle file download keys via the rewrite engine.*

```
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-download-key-(.+)/)(.+)$  
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%3,E=s2member
```

*# Handle confirmations having been skipped via the rewrite engine.*

```
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-skip-confirmation/)(.+)$  
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%2,E=s2member
```

```
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-skip-confirmation-(.+)/)(.+)$  
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%3,E=s2member
```

*# Cleanup variables not used in this request. Looking for `0` values.*

```
RewriteCond %{ENV:s2member_file_download_wp_vdir} ^0$  
RewriteRule ^(.*)$ - [E=s2member_file_download_wp_vdir:]
```

```
RewriteCond %{ENV:s2member_file_stream} ^0$  
RewriteRule ^(.*)$ - [E=s2member_file_stream:]
```

```
RewriteCond %{ENV:s2member_file_inline} ^0$  
RewriteRule ^(.*)$ - [E=s2member_file_inline:]
```

```
RewriteCond %{ENV:s2member_file_storage} ^0$  
RewriteRule ^(.*)$ - [E=s2member_file_storage:]
```

```
RewriteCond %{ENV:s2member_file_remote} ^0$  
RewriteRule ^(.*)$ - [E=s2member_file_remote:]
```

```
RewriteCond %(ENV: s2member_file_ssl) ^0$
RewriteRule ^(.*)$ - [E=s2member_file_ssl:]
```

```
RewriteCond %(ENV: s2member_file_download_key) ^0$
RewriteRule ^(.*)$ - [E=s2member_file_download_key:]
```

```
RewriteCond %(ENV: s2member_skip_confirmation) ^0$
RewriteRule ^(.*)$ - [E=s2member_skip_confirmation:]
```

*# Put everything together now and process the internal rewrite.*

```
RewriteRule ^(.*)$ %(ENV: s2member_file_download_wp_vdir)?s2member_file_download=%(ENV: s2m:
%(ENV: s2member_skip_confirmation) [QSA, L]
</IfModule>
```

```
<IfModule !rewrite_module>
  <IfModule authz_core_module>
    Require all denied
  </IfModule>
  <IfModule !authz_core_module>
    deny from all
  </IfModule>
</IfModule>
```

*# Disallow directory indexing here.*

```
Options -Indexes
```