

```
#####
## overrides deployment configuration mode value
## use command bin/magento deploy:mode:set to switch modes

# SetEnv MAGE_MODE developer

#####
## uncomment these lines for CGI mode
## make sure to specify the correct cgi php binary file name
## it might be /cgi-bin/php-cgi

# Action php5-cgi /cgi-bin/php5-cgi
# AddHandler php5-cgi .php

#####
## GoDaddy specific options

# Options -MultiViews

## you might also need to add this line to php.ini
## cgi.fix_pathinfo = 1
## if it still doesn't work, rename php.ini to php5.ini

#####
## this line is specific for 1and1 hosting

#AddType x-mapp-php5 .php
#AddHandler x-mapp-php5 .php

#####
## default index file

DirectoryIndex index.php

<IfModule mod_php5.c>

#####
## adjust memory limit

php_value memory_limit 768M
--> <!-- --> <!-- --> 1000
```

```
php_value max_execution_time 10000

#####
## disable automatic session start
## before autoload was initialized

php_flag session.auto_start off

#####
## enable resulting html compression

#php_flag zlib.output_compression on

#####
## disable user agent verification to not break multiple image upload

php_flag suhosin.session.encrypt off

</IfModule>

<IfModule mod_security.c>
#####
## disable POST processing to not break multiple image upload

    SecFilterEngine Off
    SecFilterScanPOST Off
</IfModule>

<IfModule mod_deflate.c>

#####
## enable apache served files compression
## http://developer.yahoo.com/performance/rules.html#gzip

    # Insert filter on all content
    ##SetOutputFilter DEFLATE
    # Insert filter on selected content types only
    #AddOutputFilterByType DEFLATE text/html text/plain text/xml text/css text/javascript

    # Netscape 4.x has some problems...
    #BrowserMatch ^Mozilla/4 gzip-only-text/html

```

```
# Netscape 4.06-4.08 have some more problems
#BrowserMatch ^Mozilla/4\.[0678] no-gzip

# MSIE masquerades as Netscape, but it is fine
#BrowserMatch \bMSIE !no-gzip !gzip-only-text/html

# Don't compress images
#SetEnvIfNoCase Request_URI \.(?: gif|jpe?g|png)$ no-gzip dont-vary

# Make sure proxies don't deliver the wrong content
#Header append Vary User-Agent env=!dont-vary

</IfModule>

<IfModule mod_ssl.c>

#####
## make HTTPS env vars available for CGI mode

SSLOptions StdEnvVars

</IfModule>

<IfModule mod_rewrite.c>

#####
## enable rewrites

Options +FollowSymLinks
RewriteEngine on

#####
## you can put here your magento root folder
## path relative to web root

#RewriteBase /magento/

#####
## workaround for HTTP authorization
## in CGI environment
```

```
RewriteRule . * - [E=HTTP_AUTHORIZATION: %{HTTP: Authorization}]  
  
#####  
## TRACE and TRACK HTTP methods disabled to prevent XSS attacks  
  
RewriteCond %{REQUEST_METHOD} ^TRACE  
RewriteRule . * - [L, R=405]  
  
#####  
## redirect for mobile user agents  
  
#RewriteCond %{REQUEST_URI} !^/mobilizedirectoryhere/.+  
#RewriteCond %{HTTP_USER_AGENT} "android|blackberry|ipad|iphone|ipod|iemobile|opera  
mobile|palms|webos|googlebot-mobile" [NC]  
#RewriteRule ^(.*)$ /mobilizedirectoryhere/ [L, R=302]  
  
#####  
## never rewrite for existing files, directories and links  
  
RewriteCond %{REQUEST_FILENAME} !-f  
RewriteCond %{REQUEST_FILENAME} !-d  
RewriteCond %{REQUEST_FILENAME} !-l  
  
#####  
## rewrite everything else to index.php  
  
RewriteRule . * index.php [L]  
  
</IfModule>  
  
#####  
## Prevent character encoding issues from server overrides  
## If you still have problems, use the second line instead  
  
AddDefaultCharset Off  
#AddDefaultCharset UTF-8  
  
<IfModule mod_expires.c>  
  
#####
```

```
## Add default Expires header
## http://developer.yahoo.com/performance/rules.html#expires

ExpiresDefault "access plus 1 year"
ExpiresByType text/html A0
ExpiresByType text/plain A0

</IfModule>

#####
## Deny access to root files to hide sensitive application information
RedirectMatch 404 /\.git

<Files composer.json>
    order allow,deny
    deny from all
</Files>
<Files composer.lock>
    order allow,deny
    deny from all
</Files>
<Files .gitignore>
    order allow,deny
    deny from all
</Files>
<Files .htaccess>
    order allow,deny
    deny from all
</Files>
<Files .htaccess.sample>
    order allow,deny
    deny from all
</Files>
<Files .php_cs>
    order allow,deny
    deny from all
</Files>
<Files .travis.yml>
    order allow,deny
    deny from all
</Files>
```

```
<Files CHANGELOG.md>
    order allow,deny
    deny from all
</Files>
<Files CONTRIBUTING.md>
    order allow,deny
    deny from all
</Files>
<Files CONTRIBUTOR_LICENSE AGREEMENT.html>
    order allow,deny
    deny from all
</Files>
<Files COPYING.txt>
    order allow,deny
    deny from all
</Files>
<Files Gruntfile.js>
    order allow,deny
    deny from all
</Files>
<Files LICENSE.txt>
    order allow,deny
    deny from all
</Files>
<Files LICENSE_AFL.txt>
    order allow,deny
    deny from all
</Files>
<Files nginx.conf.sample>
    order allow,deny
    deny from all
</Files>
<Files package.json>
    order allow,deny
    deny from all
</Files>
<Files php.ini.sample>
    order allow,deny
    deny from all
</Files>
<Files README.md>
```

```
order allow,deny
deny from all
</Files>

#####
## If running in cluster environment, uncomment this
## http://developer.yahoo.com/performance/rules.html#etags

#FileETag none

#####
## Add custom headers
<IfModule mod_headers.c>
    Header set X-Content-Type-Options "nosniff"
    Header set X-XSS-Protection "1; mode=block"
</IfModule>
```