

ErrorDocument 403 /error.php

ErrorDocument 404 /error.php

php_value include_path ".: /path/to/hackthis.co.uk/files/"

php_value short_open_tag "1"

```
# -----  
# | Redirects |  
# -----
```

RewriteEngine On

#STUFF

RewriteRule ^terms/?\$ /terms.php [L]

RewriteRule ^privacy/?\$ /privacy.php [L]

RewriteRule ^faq/?\$ /faq.php [L]

RewriteRule ^contact/?\$ /contact.php [L]

#IMAGES

RewriteRule ^users/images/(.+)/(.+)/(.+)\$ /files/vendor/slir/?h=\$1&c=\$2&i=\$3 [L]

RewriteRule ^images/(.+)/(.+)/(.+)\$ /files/vendor/slir/?h=\$1&c=\$2&i=\$3 [L]

RewriteRule ^files/media/images/articles/(.+)/(.+)/(.+).jpg\$ /files/vendor/slir/?i=\$3 [L]

#NEWS

RewriteRule ^news/?\$ /news.php?%(QUERY_STRING)

RewriteRule ^news/(.+)/\$ /news.php?slug=\$1&%(QUERY_STRING)

#ARTICLES

RewriteRule ^articles/contributors\$ /articles/contributors.php?%(QUERY_STRING) [L]

RewriteRule ^articles/(.+)/(.+)/([0-9]+)\$ /articles/index.php?slug=\$1/\$2&page=\$3&%(QUERY_STRING) [L]

RewriteRule ^articles/(.+)/([0-9]+)\$ /articles/index.php?slug=\$1&page=\$2&%(QUERY_STRING) [L]

RewriteRule ^articles/([0-9]+)\$ /articles/index.php?page=\$1&%(QUERY_STRING) [L]

RewriteRule ^articles/submit\$ /articles/me/submit.php?slug=\$1&%(QUERY_STRING)

RewriteCond %(REQUEST_FILENAME) !-d

RewriteCond %(REQUEST_FILENAME) !-f

RewriteRule ^articles/(.+)/(.+)/\$ /articles/index.php?slug=\$1/\$2&%(QUERY_STRING) [L]

RewriteCond %(REQUEST_FILENAME) !-d

RewriteCond %(REQUEST_FILENAME) !-f

RewriteRule ^articles/(.+)/([0-9]+)\$ /articles/index.php?slug=\$1&page=\$2&%(QUERY_STRING)

```
RewriteRule articles/(, +)?$ /articles/view.php?slug=$1&%(QUERY_STRING)
```

#FORUM

```
RewriteRule ^forum/(, +)/(, +)/([0-9]+)$ /forum/index.php?slug=$1/$2&page=$3&%(QUERY_STRING) [L]
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteRule ^forum/(, +)/(, +)$ /forum/index.php?slug=$1/$2&%(QUERY_STRING) [L]
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteRule ^forum/(, +)$ /forum/index.php?slug=$1&%(QUERY_STRING)
```

#LEVELS

```
RewriteRule ^levels/b3.php$ /levels/level.php?group=basic&level=3&%(QUERY_STRING) [L]
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteRule ^levels/(, +)/([a-zA-Z0-9]+)/?$ /levels/level.php?group=$1&level=$2&%(QUERY_STRING) [L]
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteRule ^levels/([a-zA-Z0-9]+)/?$ /levels/index.php?group=$1&%(QUERY_STRING) [L]
```

```
RewriteRule ^levels/main/extras/ssap.xml$ /levels/extras/ssap.xml [L]
```

USERS

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteRule ^user/(, +)/friends$ /user/index.php?user=$1&friends&%(QUERY_STRING) [L]
```

```
RewriteRule ^user/(, +)/userbar.png$ /user/userbar.php?user=$1 [L]
```

```
RewriteRule ^user/userbar.png$ /user/userbar.php [L]
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteRule ^user/(, +)$ /user/index.php?user=$1&%(QUERY_STRING)
```

INBOX

```
RewriteRule ^inbox/([0-9]+)$ /inbox/?view=$1&%(QUERY_STRING) [L]
```

```
RewriteRule ^inbox/compose$ /inbox/?compose&%(QUERY_STRING) [L]
```

API

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteRule ^api/(, +)$ /api/$1&%(QUERY_STRING)
```

```
RewriteRule ^api/?$ /handle_api.php?%(QUERY_STRING)

# INBOX
RewriteRule ^inbox/([0-9]+)$ /inbox/?view=$1&%(QUERY_STRING) [L]
RewriteRule ^inbox/compose$ /inbox/?compose&%(QUERY_STRING) [L]

# -----
# | Proper MIME types for all files |
# -----

<IfModule mod_mime.c>

# Audio
AddType audio/mp4 m4a f4a f4b
AddType audio/ogg oga ogg

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways):
# http://tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript js jsonp
AddType application/json json

# Video
AddType video/mp4 mp4 m4v f4v f4p
AddType video/ogg ogv
AddType video/webm webm
AddType video/x-flv flv

# Web fonts
AddType application/font-woff woff
AddType application/vnd.ms-fontobject eot

# Browsers usually ignore the font MIME types and sniff the content,
# however, Chrome shows a warning if other MIME types are used for the
# following fonts.
AddType application/x-font-ttf ttc ttf
AddType font/opentype otf

# Make SVGZ fonts work on iPad:
# https://twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml svg svgz
```

```
AddEncoding gzip svgz
```

```
# Other
```

```
AddType application/octet-stream safariextz
```

```
AddType application/x-chrome-extension crx
```

```
AddType application/x-opera-extension oex
```

```
AddType application/x-shockwave-flash swf
```

```
AddType application/x-web-app-manifest+json webapp
```

```
AddType application/x-xpinstall xpi
```

```
AddType application/xml atom rdf rss xml
```

```
AddType image/webp webp
```

```
AddType image/x-icon ico
```

```
AddType text/cache-manifest appcache manifest
```

```
AddType text/vtt vtt
```

```
AddType text/x-component htc
```

```
AddType text/x-vcard vcf
```

```
</IfModule>
```

```
# -----
```

```
# | UTF-8 encoding |
```

```
# -----
```

```
# Use UTF-8 encoding for anything served as `text/html` or `text/plain`.
```

```
AddDefaultCharset utf-8
```

```
# Force UTF-8 for certain file formats.
```

```
<IfModule mod_mime.c>
```

```
    AddCharset utf-8 .atom .css .js .json .rss .vtt .webapp .xml
```

```
</IfModule>
```

```
# -----
```

```
# | File access |
```

```
# -----
```

```
# Block access to directories without a default document.
```

```
# Usually you should leave this uncommented because you shouldn't allow anyone
```

```
# to surf through every directory on your server (which may includes rather
```

```
# private places like the CMS' s directories).
```

```
<IfModule mod_autoindex.c>
```

Options -Indexes

</IfModule>

Block access to hidden files and directories.

This includes directories used by version control systems such as Git and SVN.

<IfModule mod_rewrite.c>

RewriteCond %{SCRIPT_FILENAME} -d [OR]

RewriteCond %{SCRIPT_FILENAME} -f

RewriteRule "(^/)\." - [F]

</IfModule>

Block access to backup and source files.

These files may be left by some text editors and can pose a great security

danger when anyone has access to them.

<FilesMatch "(^#.#|\. (bak| config| dist| fl| incl| ini| log| psd| sh| sql| sw[op])| (^)\$">

Order allow,deny

Deny from all

Satisfy All

</FilesMatch>

php_value session.cookie_httponly true

<ifModule mod_deflate.c>

<filesMatch "\.(js|css|php)\$">

SetOutputFilter DEFLATE

</filesMatch>

</ifModule>

<ifModule mod_expires.c>

ExpiresActive On

ExpiresDefault "access plus 1 seconds"

ExpiresByType text/html "access plus 1 seconds"

ExpiresByType image/gif "access plus 2592000 seconds"

ExpiresByType image/jpeg "access plus 2592000 seconds"

ExpiresByType image/png "access plus 2592000 seconds"

```
ExpiresByType text/css "access plus 604800 seconds"
ExpiresByType text/javascript "access plus 216000 seconds"
ExpiresByType application/x-javascript "access plus 216000 seconds"
</ifModule>

<ifModule mod_headers.c>
  <filesMatch "\\.(ico|pdf|flv|jpg|jpeg|png|gif|swf)$">
    Header set Cache-Control "max-age=2592000, public"
  </filesMatch>
  <filesMatch "\\.(css)$">
    Header set Cache-Control "max-age=60, public"
  </filesMatch>
  <filesMatch "\\.(js)$">
    Header set Cache-Control "max-age=60, private"
  </filesMatch>
  <filesMatch "\\.(xml|txt)$">
    Header set Cache-Control "max-age=216000, public, must-revalidate"
  </filesMatch>
  <filesMatch "\\.(html|html|php)$">
    Header set Cache-Control "max-age=1, private, must-revalidate"
  </filesMatch>
</ifModule>

<IfModule mod_php4.c>
  php_value magic_quotes_gpc off
</IfModule>
```