```
RewriteEngine on

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^(.*)$ /index.php

# if you install in a subdirectory, be sure to include the entire path, relative to
DocumentRoot
# for example, ErrorDocument 404 /icms/error.php?e=404

ErrorDocument 400 /error.php?e=400
ErrorDocument 401 /error.php?e=401
ErrorDocument 402 /error.php?e=402
ErrorDocument 403 /error.php?e=403
# Below line is commented because same functionality is handled by index.php
# ErrorDocument 404 /error.php?e=404
ErrorDocument 405 /error.php?e=405
ErrorDocument 406 /error.php?e=406
ErrorDocument 407 /error.php?e=407
ErrorDocument 408 /error.php?e=408
ErrorDocument 409 /error.php?e=409
ErrorDocument 410 /error.php?e=410
ErrorDocument 411 /error.php?e=411
ErrorDocument 412 /error.php?e=412
ErrorDocument 413 /error.php?e=413
ErrorDocument 414 /error.php?e=414
ErrorDocument 415 /error.php?e=415
ErrorDocument 416 /error.php?e=416
ErrorDocument 417 /error.php?e=417
ErrorDocument 500 /error.php?e=500
ErrorDocument 501 /error.php?e=501
ErrorDocument 502 /error.php?e=502
ErrorDocument 503 /error.php?e=503
ErrorDocument 504 /error.php?e=504
ErrorDocument 505 /error.php?e=505

RewriteCond %{QUERY_STRING} base64_encode[^(]*\([^)]*\) [OR]
RewriteCond %{QUERY_STRING} (<|%3C)([^s]*s)+cript.*(>|%3E) [NC,OR]
RewriteCond %{QUERY_STRING} GLOBALS(=|\[|\%[0-9A-Z]{0,2}) [OR]
RewriteCond %{QUERY_STRING} _REQUEST(=|\[|\%[0-9A-Z]{0,2})
```

```
RewriteRule .* index.php [F,L]


RewriteRule ^templates_c/(.*)$ index.php [F,L]
RewriteRule ^themes/(.*)\.php$ index.php [F,L]
```