

```
#
# Apache/PHP/Drupal settings:
#

# Protect files and directories from prying eyes.
<Files ~ "(\\.
(incl module| pl| sh| sql| theme| engine| xtmp|) | Entries| Repositories| Root| scripts| updates)$">
    Order deny, allow
    Deny from all
</Files>

# Set some options.
Options -Indexes
Options +FollowSymLinks

# Customized error messages.
ErrorDocument 404 /index.php

# Set the default handler.
DirectoryIndex index.php

# Override PHP settings. More exist in sites/default/settings.php, but
# the following cannot be changed at runtime. The first IfModule is
# for Apache 1.3, the second for Apache 2.
<IfModule mod_php4.c>
    php_value magic_quotes_gpc          0
    php_value register_globals          0
    php_value session.auto_start        0
</IfModule>

<IfModule sapi_apache2.c>
    php_value magic_quotes_gpc          0
    php_value register_globals          0
    php_value session.auto_start        0
</IfModule>

# Reduce the time dynamically generated pages are cache-able.
<IfModule mod_expires.c>
    ExpiresByType text/html A1
</IfModule>
```

```

# Various rewrite rules.
<IfModule mod_rewrite.c>
  RewriteEngine on

  # Modify the RewriteBase if you are using Drupal in a subdirectory and
  # the rewrite rules are not working properly.
  #RewriteBase /drupal

  ### BOOST START ###
  AddDefaultCharset utf-8
  <FilesMatch "(\\.html|\\.html\\.gz)$">
    <IfModule mod_headers.c>
      Header set Expires "Sun, 19 Nov 1978 05:00:00 GMT"
      Header set Cache-Control "no-store, no-cache, must-revalidate, post-check=0, pre-
check=0"
    </IfModule>
  </FilesMatch>
  <IfModule mod_mime.c>
    AddCharset utf-8 .html
    AddCharset utf-8 .css
    AddCharset utf-8 .js
    AddEncoding gzip .gz
  </IfModule>
  <FilesMatch "(\\.html|\\.html\\.gz)$">
    ForceType text/html
  </FilesMatch>
  <FilesMatch "(\\.js|\\.js\\.gz)$">
    ForceType text/javascript
  </FilesMatch>
  <FilesMatch "(\\.css|\\.css\\.gz)$">
    ForceType text/css
  </FilesMatch>

  # Gzip Cookie Test
  RewriteRule boost-gzip-cookie-test\\.html cache/perm/boost-gzip-cookie-test\\.html\\.gz
  [L,T=text/html]

  # GZIP - Cached css & js files
  RewriteCond %{HTTP_COOKIE} !(boost-gzip)
  RewriteRule ^/(.*)\\.css$ $1\\.gz [L]
  RewriteRule ^/(.*)\\.js$ $1\\.gz [L]

```

```

RewriteCond %{HTTP: Accept-encoding} !gzip
RewriteRule .* - [S=2]
RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\.css\.gz -s
RewriteRule .* cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\.css\.gz [L, QSA, T=text/css]
RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\.js\.gz -s
RewriteRule .* cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\.js\.gz
[L, QSA, T=text/javascript]

# NORMAL - Cached css & js files
RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\.css -s
RewriteRule .* cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\.css [L, QSA, T=text/css]
RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\.js -s
RewriteRule .* cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\.js [L, QSA, T=text/javascript]

# Caching for anonymous users
# Skip boost IF not get request OR uri has wrong dir OR cookie is set OR request came
from this server OR https request
RewriteCond %{REQUEST_METHOD} !^(GET|HEAD)$ [OR]
RewriteCond %{REQUEST_URI}
(^/(admin|cache|misc|modules|sites|system|openid|themes|node/add))|
(/(comment/reply|edit|user|user/(login|password|register)))$ [OR]
RewriteCond %{HTTP_COOKIE} DRUPAL_UID [OR]
RewriteCond %{HTTP: Pragma} no-cache [OR]
RewriteCond %{HTTP: Cache-Control} no-cache [OR]
RewriteCond %{HTTPS} on
RewriteRule .* - [S=3]

# GZIP
RewriteCond %{HTTP_COOKIE} !(boost-gzip)
RewriteCond %{HTTP: Accept-encoding} !gzip
RewriteRule .* - [S=1]
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%
{QUERY_STRING}\.html\.gz -s
RewriteRule .* cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{QUERY_STRING}\.html\.gz
[L, T=text/html]

# NORMAL
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%
{QUERY_STRING}\.html -s
RewriteRule .* cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{QUERY_STRING}\.html
[L, T=text/html]

```

```
### BOOST END ###
```

```
RewriteCond %{HTTP_HOST} ^www\.(.+) [NC]  
RewriteRule ^(.*)$ http://%1%{REQUEST_URI} [L,R=301]
```

```
# Rewrite old-style URLs of the form 'node.php?id=x'.
```

```
#RewriteCond %{REQUEST_FILENAME} !-f  
#RewriteCond %{REQUEST_FILENAME} !-d  
#RewriteCond %{QUERY_STRING} ^id=(.*)$  
#RewriteRule node.php index.php?q=node/view/%1 [L]
```

```
# Rewrite old-style URLs of the form 'module.php?mod=x'.
```

```
#RewriteCond %{REQUEST_FILENAME} !-f  
#RewriteCond %{REQUEST_FILENAME} !-d  
#RewriteCond %{QUERY_STRING} ^mod=(.*)$  
#RewriteRule module.php index.php?q=%1 [L]
```

```
# Rewrite current-style URLs of the form 'index.php?q=x'.
```

```
RewriteCond %{REQUEST_FILENAME} !-f  
RewriteCond %{REQUEST_FILENAME} !-d  
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
```

```
</IfModule>
```

```
# $Id: .htaccess,v 1.66 2005/03/20 19:15:00 dries Exp $
```