

```
# This turns on mod_rewrite and redirects any paths that don't physically exist
# to /index.php. You can then access that path info (to determine what to do) in
# PHP using $_SERVER['REQUEST_URI'] and $_SERVER['REDIRECT_URL']. This is an easy
# way to avoid having hundreds of rewrite rules slowing down Apache and making things
# more complicated than they should be.
#don't forget to un comment !
# Note: If you're having trouble making Apache pickup your .htaccess file,
# make sure AllowOverride is set to "All" instead of "None".
```

```
# RewriteEngine On
```

```
# RewriteBase /
```

```
<IfModule mod_headers.c>
```

```
# WEEK
```

```
<FilesMatch "\.(j|jpg|jpeg|png|gif|swf|js|css)$">
```

```
Header set Cache-Control "max-age=604800, public"
```

```
</FilesMatch>
```

```
<IfModule mod_deflate.c>
```

```
AddOutputFilterByType DEFLATE text/html
```

```
AddOutputFilterByType DEFLATE text/css
```

```
AddOutputFilterByType DEFLATE text/javascript
```

```
AddOutputFilterByType DEFLATE text/xml
```

```
AddOutputFilterByType DEFLATE text/plain
```

```
AddOutputFilterByType DEFLATE image/x-icon
```

```
AddOutputFilterByType DEFLATE image/svg+xml
```

```
AddOutputFilterByType DEFLATE application/rss+xml
```

```
AddOutputFilterByType DEFLATE application/javascript
```

```
AddOutputFilterByType DEFLATE application/x-javascript
```

```
AddOutputFilterByType DEFLATE application/xml
```

```
AddOutputFilterByType DEFLATE application/xhtml+xml
```

```
AddOutputFilterByType DEFLATE application/x-font
```

```
AddOutputFilterByType DEFLATE application/x-font-truetype
```

```
AddOutputFilterByType DEFLATE application/x-font-ttf
```

```
AddOutputFilterByType DEFLATE application/x-font-otf
```

```
AddOutputFilterByType DEFLATE application/x-font-opentype
```

```
AddOutputFilterByType DEFLATE application/vnd.ms-fontobject
```

```
AddOutputFilterByType DEFLATE font/ttf
```

```
AddOutputFilterByType DEFLATE font/otf
```

```
AddOutputFilterByType DEFLATE font/opentype
```

```
# For Older Browsers Which Can't Handle Compression
```

```
BrowserMatch ^Mozilla/4 ssl=no gzip=no
```

```
BrowserMatch ^Mozilla/4 gzip-only-text/html
BrowserMatch ^Mozilla/4\.0[678] no-gzip
BrowserMatch \bMSIE !no-gzip !gzip-only-text/html
</IfModule>
# RewriteCond %{REQUEST_FILENAME} !-f # If not a file...
# RewriteCond %{REQUEST_FILENAME} !-d # and not a directory...
# RewriteRule . /index.php [L] # serve index.php
RewriteEngine On
RewriteCond %{HTTPS} off
RewriteCond %{SERVER_PORT} 80
RewriteCond %{REQUEST_URI} shop
RewriteRule ^(.*)$ https://kbracing.eu/$1 [R,L]
RewriteCond %{HTTPS} off
RewriteCond %{REQUEST_URI} (shop/)
RewriteRule ^(.*)$ https://%{HTTP_HOST}/$1 [R=301,L]
```