

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine On
```

```
RewriteBase /TabularASA-projet/
```

```
# Remove www uncomment to activate
```

```
#RewriteCond %{HTTP_HOST} ^www\. (.*)$ [NC]
```

```
#RewriteRule ^(.*)$ http://%1/%1 [R=301,L]
```

```
# Force ssl uncomment to activate
```

```
#RewriteCond %{HTTPS} !on
```

```
#RewriteRule (.*) https://%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
```

```
# Allow any files or directories that exist to be displayed directly
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule ^(.*)$ index.php?$1 [QSA,L]
```

```
</IfModule>
```

```
# Remove ETags as resources are sent with far-future expires headers.
```

```
# http://developer.yahoo.com/performance/rules.html#etags.
```

```
# FileETag None doesn't work in all cases.
```

```
<IfModule mod_headers.c>
```

```
Header unset ETag
```

```
</IfModule>
```

```
FileETag None
```

```
# Force Internet Explorer to render pages in the highest available mode
```

```
# in the various cases when it may not.
```

```
# http://hsivonen.iki.fi/doctype/ie-mode.pdf
```

```
<IfModule mod_headers.c>
```

```
Header set X-UA-Compatible 'IE=edge'
```

```
# mod_headers cannot match based on the content-type, however, this
```

```
# header should be send only for HTML pages and not for the other resources
```

```
<FilesMatch "\.(appcache|atom|crx|css|curl|eot|f4[abpv]|flv|gif|html|ico|jpe?
```

```
...)
```

```
gi json jsonld?
|m4[av]|manifest|map|mp4|oexl|og[agv]|opus|otf|pdf|png|rdf|rss|safariextz|svgz?
|swf|tt[cf]|vcl|vtt|webapp|web[mp]|woff|xml|xpi)">
    Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

#turn off directory browsing
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

#compression
<IfModule mod_deflate.c>

    # Force compression for mangled headers,
    # http://developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-beyond-gzipping
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXngl|X-cept-Encodingl|X(15)|^(15)|-(15))$
            ^((gzip|deflate)\s*,?\s*)+([X"-]{4,13})$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding 'gzip,deflate' env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # Compress all output labeled with one of the following MIME-types
    # (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
    # and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
    # as `AddOutputFilterByType` is still in the core directives),
    <IfModule mod_filter.c>
        AddOutputFilterByType DEFLATE application/atom+xml \
            application/javascript \
            application/json \
            application/ld+json \
            application/rss+xml \
            application/vnd.ms-fontobject \
            application/x-font-ttf \
            application/x-web-app-manifest+json \
            application/xhtml+xml \
            application/xml \
            font/opentype \
            . . . . .
```

```
image/svg+xml \  
image/x-icon \  
text/css \  
text/html \  
text/plain \  
text/x-component \  
text/xml
```

```
</IfModule>
```

```
</IfModule>
```

```
# The following expires headers are set pretty far in the future. If you  
# don't control versioning with filename-based cache busting, consider  
# lowering the cache time for resources such as style sheets and JavaScript  
# files to something like one week.
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on  
ExpiresDefault 'access plus 1 month'
```

```
# CSS
```

```
ExpiresByType text/css 'access plus 1 year'
```

```
# Data interchange
```

```
ExpiresByType application/json 'access plus 0 seconds'
```

```
ExpiresByType application/ld+json 'access plus 0 seconds'
```

```
ExpiresByType application/xml 'access plus 0 seconds'
```

```
ExpiresByType text/xml 'access plus 0 seconds'
```

```
# Favicon (cannot be renamed!) and cursor images
```

```
ExpiresByType image/x-icon 'access plus 1 week'
```

```
# HTML components (HTCs)
```

```
ExpiresByType text/x-component 'access plus 1 month'
```

```
# HTML
```

```
ExpiresByType text/html 'access plus 0 seconds'
```

```
# JavaScript
```

```
ExpiresByType application/javascript 'access plus 1 year'
```

### # Manifest files

```
ExpiresByType application/x-web-app-manifest+json 'access plus 0 seconds'  
ExpiresByType text/cache-manifest 'access plus 0 seconds'
```

### # Media

```
ExpiresByType audio/ogg 'access plus 1 month'  
ExpiresByType image/gif 'access plus 1 month'  
ExpiresByType image/jpeg 'access plus 1 month'  
ExpiresByType image/png 'access plus 1 month'  
ExpiresByType video/mp4 'access plus 1 month'  
ExpiresByType video/ogg 'access plus 1 month'  
ExpiresByType video/webm 'access plus 1 month'
```

### # Web feeds

```
ExpiresByType application/atom+xml 'access plus 1 hour'  
ExpiresByType application/rss+xml 'access plus 1 hour'
```

### # Web fonts

```
ExpiresByType application/font-woff 'access plus 1 month'  
ExpiresByType application/vnd.ms-fontobject 'access plus 1 month'  
ExpiresByType application/x-font-ttf 'access plus 1 month'  
ExpiresByType font/opentype 'access plus 1 month'  
ExpiresByType image/svg+xml 'access plus 1 month'
```

</IfModule>