

```
<IfModule mod_headers.c>

    <FilesMatch "\.(eot|otf|tt[cf]|woff2?)$">

        Header set Access-Control-Allow-Origin "*"

    </FilesMatch>

</IfModule>

<IfModule mod_headers.c>

    Header set X-UA-Compatible "IE=edge"

    # `mod_headers` cannot match based on the content-type, however,
    # the `X-UA-Compatible` response header should be send only for
    # HTML documents and not for the other resources.

    <FilesMatch "\.
    (appcache|atom|bbaw|bmp|crx|css|curl|eot|f4[abpv]|flv|geojson|gif|htc|icol|jpe?
    |js|json|ld)?
    |m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rss|safariextz|svgz?
    |swf|topojson|tt[cf]|txt|vcard|vcf|vtt|webapp|web[mp]|webmanifest|woff2?|xloc|xml|xpi)">

        Header unset X-UA-Compatible

    </FilesMatch>

</IfModule>

# Serve resources with the proper media types (f. k. a. MIME types).
#
# https://www.iana.org/assignments/media-types/media-types.xhtml
# https://httpd.apache.org/docs/current/mod/mod_mime.html#addtype
#</pre>
```

```
<!DOCTYPE mod_mime.C>
```

```
# Data interchange
```

```
AddType application/atom+xml      atom
AddType application/json            json map topjson
AddType application/ld+json         jsonld
AddType application/rss+xml         rss
AddType application/vnd.geo+json    geojson
AddType application/xml             rdf xml
```

```
# JavaScript
```

```
# Normalize to standard type.
```

```
# https://tools.ietf.org/html/rfc4329#section-7.2
```

```
AddType application/javascript     js
```

```
# Manifest files
```

```
AddType application/manifest+json  webmanifest
AddType application/x-web-app-manifest+json webapp
AddType text/cache-manifest          appcache
```

```
# Media files
```

```
AddType audio/mp4                  f4a f4b m4a
AddType audio/ogg                    oga ogg opus
AddType image/bmp                    bmp
AddType image/svg+xml                svg svgz
```

```
AddType image/webp                                webp

AddType video/mp4                                  f4v f4p m4v mp4

AddType video/ogg                                  ogv

AddType video/webm                                  webm

AddType video/x-flv                                 flv

# Serving `.ico` image files with a different media type

# prevents Internet Explorer from displaying them as images:

# https://github.com/h5bp/html5-boilerplate/commit/37b5fec090d00f38de64b591bcddcb205aadf8ee

AddType image/x-icon                               cur ico

# Web fonts

AddType application/font-woff                      woff

AddType application/font-woff2                    woff2

AddType application/vnd.ms-fontobject              eot

# Browsers usually ignore the font media types and simply sniff

# the bytes to figure out the font type.

# https://mimesniff.spec.whatwg.org/#matching-a-font-type-pattern

#

# However, Blink and WebKit based browsers will show a warning

# in the console if the following font types are served with any

# other media types.
```

AddType application/x-font-ttf ttc ttf

AddType font/opentype otf

*# Other*

AddType application/octet-stream safariextz

AddType application/x-bb-appworld bbaw

AddType application/x-chrome-extension crx

AddType application/x-opera-extension oex

AddType application/x-xpinstall xpi

AddType text/vcard vcard vcf

AddType text/vnd.rim.location.xloc xloc

AddType text/vtt vtt

AddType text/x-component htc

</IfModule>

# -----

# | *Character encodings* |

# -----

# *Serve all resources labeled as `text/html` or `text/plain`*

# *with the media type `charset` parameter set to `UTF-8`.*

#

# <https://httpd.apache.org/docs/current/mod/core.html#adddefaultcharset>

```
AddDefaultCharset utf-8
```

```
# -----
```

```
# Serve the following file types with the media type `charset`
```

```
# parameter set to `UTF-8`.
```

```
#
```

```
# https://httpd.apache.org/docs/current/mod/mod\_mime.html#addcharset
```

```
<IfModule mod_mime.c>
```

```
    AddCharset utf-8 .atom \  
                .bbaw \  
                .css \  
                .geojson \  
                .js \  
                .json \  
                .jsonld \  
                .manifest \  
                .rdf \  
                .rss \  
                .topojson \  
                .vtt \  
                .webapp \  
                .webmanifest \  
                .xloc \  
                .xml
```

```
</IfModule>
```

```
<IfModule mod_headers.c>
```

```
    Header unset X-Powered-By
```

```
</IfModule>
```

```
<IfModule mod_deflate.c>
```

```
    <IfModule mod_setenvif.c>
```

```
<IfModule mod_headers.c>
```

```
    SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$  
    ^((gzip|deflate)\s*,?\s*)+ [X"-]{4,13}$ HAVE_Accept-Encoding
```

```
    RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_filter.c>
```

```
    AddOutputFilterByType DEFLATE "application/atom+xml" \  
        "application/javascript" \  
        "application/json" \  
        "application/ld+json" \  
        "application/manifest+json" \  
        "application/rdf+xml" \  
        "application/rss+xml" \  
        "application/schema+json" \  
        "application/vnd.geo+json" \  
        "application/vnd.ms-fontobject" \  
        "application/x-font-ttf" \  
        "application/x-javascript" \  
        "application/x-web-app-manifest+json" \  
        "application/xhtml+xml" \  
        "application/xml" \  
        "font/eot" \  
        "font/opentype" \  
        "image/bmp" \  
        "image/svg+xml" \  
        "image/vnd.microsoft.icon" \  
        "image/x-icon" \  
        "text/cache-manifest" \  
        "text/css" \  
        "text/html" \  
        "text/javascript" \  
        "text/plain" \  
        "text/vcard" \  
        "text/vnd.rim.location.xloc" \  
        "text/x-yaml"
```

```
"text/vtt" \  
"text/x-component" \  
"text/x-cross-domain-policy" \  
"text/xml"
```

```
</IfModule>
```

```
<IfModule mod_mime.c>
```

```
    AddEncoding gzip          svgz
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_headers.c>
```

```
    Header unset ETag
```

```
</IfModule>
```

```
## BEGIN Expires Caching (Leverage Browser Caching) ##
```

```
<IfModule mod_expires.c>
```

```
    ExpiresActive on
```

```
    ExpiresDefault          "access plus 1 month"
```

```
# CSS
```

```
    ExpiresByType text/css          "access plus 1 year"
```

```
# Data interchange
```

```
    ExpiresByType application/atom+xml          "access plus 1 hour"
```

```
    ExpiresByType application/rdf+xml          "access plus 1 hour"
```

```
    ExpiresByType application/rss+xml          "access plus 1 hour"
```

```
ExpiresByType application/json "access plus 0 seconds"

ExpiresByType application/ld+json "access plus 0 seconds"

ExpiresByType application/schema+json "access plus 0 seconds"

ExpiresByType application/vnd.geo+json "access plus 0 seconds"

ExpiresByType application/xml "access plus 0 seconds"

ExpiresByType text/xml "access plus 0 seconds"
```

*# Favicon (cannot be renamed!) and cursor images*

```
ExpiresByType image/vnd.microsoft.icon "access plus 1 week"

ExpiresByType image/x-icon "access plus 1 week"
```

*# HTML*

```
ExpiresByType text/html "access plus 0 seconds"
```

*# JavaScript*

```
ExpiresByType application/javascript "access plus 1 year"

ExpiresByType application/x-javascript "access plus 1 year"

ExpiresByType text/javascript "access plus 1 year"
```

*# Manifest files*

```
ExpiresByType application/manifest+json "access plus 1 week"

ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"

ExpiresByType text/cache-manifest "access plus 0 seconds"
```

*# Media files*

```
ExpiresByType audio/ogg "access plus 1 month"
```



~~ExpiresByType image/gif~~

~~----- plus 1 month~~

ExpiresByType image/bmp

"access plus 1 month"

ExpiresByType image/gif

"access plus 1 month"

ExpiresByType image/jpeg

"access plus 1 month"

ExpiresByType image/png

"access plus 1 month"

ExpiresByType image/svg+xml

"access plus 1 month"

ExpiresByType image/webp

"access plus 1 month"

ExpiresByType video/mp4

"access plus 1 month"

ExpiresByType video/ogg

"access plus 1 month"

ExpiresByType video/webm

"access plus 1 month"

### *# Web fonts*

#### *# Embedded OpenType (EOT)*

ExpiresByType application/vnd.ms-fontobject

"access plus 1 month"

ExpiresByType font/eot

"access plus 1 month"

#### *# OpenType*

ExpiresByType font/opentype

"access plus 1 month"

#### *# TrueType*

ExpiresByType application/x-font-ttf

"access plus 1 month"

#### *# Web Open Font Format (WOFF) 1.0*

ExpiresByType application/font-woff

"access plus 1 month"

ExpiresByType application/x-font-woff

"access plus 1 month"

```
ExpiresByType font/woff "access plus 1 month"

# Web Open Font Format (WOFF) 2.0
ExpiresByType application/font-woff2 "access plus 1 month"

# Other
ExpiresByType text/x-cross-domain-policy "access plus 1 week"

</IfModule>

## END Expires Caching (Leverage Browser Caching) ##

## BEGIN Enable GZIP Compression ##

## END Enable GZIP Compression ##

## BEGIN Vary: Accept-Encoding Header ##

<IfModule mod_headers.c>

<FilesMatch "\.(js|css|xml|gz)$">

Header append Vary: Accept-Encoding

</FilesMatch>

</IfModule>

## END Vary: Accept-Encoding Header ##

<IfModule mod_rewrite.c>

RewriteEngine On

RewriteCond %{REQUEST_URI} !/web/

RewriteRule ^ /web/ [R=301,L]
```

```
RewriteRule ^(.*) /web/$1 [L]
```

```
RewriteBase /
```

```
RewriteRule ^index\.php$ - [L]
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule . /web/index.php [L]
```

```
RewriteRule ^([\_0-9a-zA-Z]+)/wp-admin$ $1wp-admin/ [R=301,L]
```

```
</IfModule>
```

```
AddHandler application/x-httpd-php56 .php .php5 .php4 .php3
```