

```
# Use the front controller as index file. It serves as a fallback solution when
# every other rewrite/redirect fails (e.g. in an aliased environment without
# mod_rewrite). Additionally, this reduces the matching process for the
# start page (path "/") because otherwise Apache will apply the rewriting rules
# to each configured DirectoryIndex file (e.g. index.php, index.html, index.pl).
DirectoryIndex app_dev.php
```

```
<IfModule mod_rewrite.c>
```

```
    RewriteEngine On
```

```
    # Fix for Apache server, that chops off Authorization header.
```

```
    RewriteCond %{HTTP:Authorization} ^(.*)
```

```
    RewriteRule .* - [e=HTTP_AUTHORIZATION:%1]
```

```
    # Determine the RewriteBase automatically and set it as environment variable.
```

```
    # If you are using Apache aliases to do mass virtual hosting or installed the
```

```
    # project in a subdirectory, the base path will be prepended to allow proper
```

```
    # resolution of the app_dev.php file and to redirect to the correct URI. It will
```

```
    # work in environments without path prefix as well, providing a safe, one-size
```

```
    # fits all solution. But as you do not need it in this case, you can comment
```

```
    # the following 2 lines to eliminate the overhead.
```

```
    RewriteCond %{REQUEST_URI}::$1 ^(/.+)/(.*):\2$
```

```
    RewriteRule ^(.*) - [E=BASE:%1]
```

```
    # Redirect to URI without front controller to prevent duplicate content
```

```
    # (with and without `app_dev.php`). Only do this redirect on the initial
```

```
    # rewrite by Apache and not on subsequent cycles. Otherwise we would get an
```

```
    # endless redirect loop (request -> rewrite to front controller ->
```

```
    # redirect -> request -> ...).
```

```
    # So in case you get a "too many redirects" error or you always get redirected
```

```
    # to the start page because your Apache does not expose the REDIRECT_STATUS
```

```
    # environment variable, you have 2 choices:
```

```
    # - disable this feature by commenting the following 2 lines or
```

```
    # - use Apache >= 2.3.9 and replace all L flags by END flags and remove the
```

```
    # following RewriteCond (best solution)
```

```
    RewriteCond %{ENV:REDIRECT_STATUS} ^$
```

```
    RewriteRule ^app\.(php|html)$ %ENV:BASE/$2 [R=301,L]
```

```
    # If the requested filename exists, simply serve it.
```

```
    # We only want to let Apache serve files and not directories.
```

```
    RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule .? - [L]

# Rewrite all other queries to the front controller.
RewriteRule .? %{ENV:BASE}/app_dev.php [L]
</IfModule>

<IfModule !mod_rewrite.c>
  <IfModule mod_alias.c>
    # When mod_rewrite is not available, we instruct a temporary redirect of
    # the start page to the front controller explicitly so that the website
    # and the generated links can still be used.
    RedirectMatch 302 ^/$ /app_dev.php/
    # RedirectTemp cannot be used instead
  </IfModule>
</IfModule>
```