

```
# Use PHP5.4 as default
AddHandler application/x-httpd-php54 .php
# Changed PHP handler from application/x-httpd-php5s to application/x-httpd-phpbetas on
Mon Jan 11 11:02:59 MST 2016.
#
# Apache/PHP/Drupal settings:
#

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engine|incl|info|install|make|module|profile|test|po|sh|. *sql|themel|tpl(\.php)?|x|tmp|svn-
base)$|^(\code-style|.p|Entries.*|Repository|Root|Tag|Template|all-
wcprops|entries|format)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
# For security reasons, Option followsymlinks cannot be overridden.
#Options +FollowSymLinks
Options +SymLinksIfOwnerMatch

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Set the default handler.
DirectoryIndex index.php

# Override PHP settings. More in sites/default/settings.php
# but the following cannot be changed at runtime.

# PHP 4, Apache 1.
<#MIMEMap - add php4 as
```

```

<IfModule mod_php4.c>
    php_value magic_quotes_gpc            0
    php_value register_globals            0
    php_value session.auto_start         0
    php_value mbstring.http_input        pass
    php_value mbstring.http_output       pass
    php_value mbstring.encoding_translation 0
</IfModule>

# PHP 4, Apache 2.
<IfModule sapi_apache2.c>
    php_value magic_quotes_gpc            0
    php_value register_globals            0
    php_value session.auto_start         0
    php_value mbstring.http_input        pass
    php_value mbstring.http_output       pass
    php_value mbstring.encoding_translation 0
</IfModule>

# PHP 5, Apache 1 and 2.
<IfModule mod_php5.c>
    php_value magic_quotes_gpc            0
    php_value register_globals            0
    php_value session.auto_start         0
    php_value mbstring.http_input        pass
    php_value mbstring.http_output       pass
    php_value mbstring.encoding_translation 0
</IfModule>

# Requires mod_expires to be enabled.
<IfModule mod_expires.c>
    # Enable expirations.
    ExpiresActive On

    # Cache all files for 2 weeks after access (A).
    ExpiresDefault A1209600

<FilesMatch \.php$>
    # Do not allow PHP scripts to be cached unless they explicitly send cache
    # headers themselves. Otherwise all scripts would have to overwrite the
    # headers set by mod_expires if they want another caching behavior. This may
    # not be desirable for all cases, but it prevents some common ones.

```

```
# fail if an error occurs early in the bootstrap process, and it may cause
# problems if a non-Drupal PHP file is installed in a subdirectory.
ExpiresActive Off
</FilesMatch>
</IfModule>

# Various rewrite rules.
<IfModule mod_rewrite.c>
  RewriteEngine on

  # If your site can be accessed both with and without the 'www.' prefix, you
  # can use one of the following settings to redirect users to your preferred
  # URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
  #
  # To redirect all users to access the site WITH the 'www.' prefix,
  # (http://example.com/... will be redirected to http://www.example.com/...)
  # adapt and uncomment the following:
  # RewriteCond %{HTTP_HOST} ^example\.com$ [NC]
  # RewriteRule ^(.*)$ http://www.example.com/$1 [L,R=301]
  #
  # To redirect all users to access the site WITHOUT the 'www.' prefix,
  # (http://www.example.com/... will be redirected to http://example.com/...)
  # uncomment and adapt the following:
  # RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]
  # RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]

  # Add the following lines as per HostGator instructions
  RewriteCond %{SERVER_PORT} 80
  RewriteRule ^(.*)$ https://%{HTTP_HOST}%{REQUEST_URI} [L,R=301]

  # Modify the RewriteBase if you are using Drupal in a subdirectory or in a
  # VirtualDocumentRoot and the rewrite rules are not working properly.
  # For example if your site is at http://example.com/drupal uncomment and
  # modify the following line:
  # RewriteBase /drupal
  #
  # If your site is running in a VirtualDocumentRoot at http://example.com/,
  # uncomment the following line:
  # RewriteBase /

  # Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
```

```
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} !=/favicon.ico
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
</IfModule>
```

```
# $Id: .htaccess,v 1.90.2.5 2010/02/02 07:25:22 dries Exp $
```