

```

<IfModule mod_rewrite.c>
  <IfModule mod_negotiation.c>
    Options -MultiViews
  </IfModule>
  <IfModule mod_headers.c>
    Header set Access-Control-Allow-Origin: *
  </IfModule>
  RewriteEngine On

  # Redirect Trailing Slashes...
  RewriteRule ^(.*)/$ /$1 [L,R=301]

  # Handle Front Controller...
  RewriteCond %{REQUEST_FILENAME} !-d
  RewriteCond %{REQUEST_FILENAME} !-f
  RewriteRule ^ index.php [L]
</IfModule>

# -----
# | Compression |
# -----

<IfModule mod_deflate.c>

  # Force compression for mangled headers.
  # http://developer.yahoo.com/blogs/ymdn/posts/2010/12/pushing-beyond-gzipping
  <IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
      SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
      ^((gzip|deflate)\s*,?\s*)+([X"-]{4,13})$ HAVE_Accept-Encoding
      RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
    </IfModule>
  </IfModule>

  # Compress all output labeled with one of the following MIME-types
  # (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
  # and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
  # as `AddOutputFilterByType` is still in the core directives).
  <IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
      application/javascript \
      application/json \
      application/rss+xml \
      application/vnd.mozilla.xul+xml \
      application/xml \
      application/zip \
      image/svg+xml \
      image/x-icon \
      text/css \
      text/html \
      text/xml \
      text/xsl \
      text/plain \
      text/xml
  </IfModule>

```

```
application/javascript \  
application/json \  
application/ld+json \  
application/rss+xml \  
application/vnd.ms-fontobject \  
application/x-font-ttf \  
application/x-web-app-manifest+json \  
application/xhtml+xml \  
application/xml \  
font/opentype \  
image/svg+xml \  
image/x-icon \  
text/css \  
text/html \  
text/plain \  
text/x-component \  
text/xml
```

</IfModule>

</IfModule>