

```

#
# $Id$
#
# Handle request routing,
#

# PHP settings
#
php_value short_open_tag 0
php_flag magic_quotes_gpc Off

# Redirection (requires the "mod_rewrite" Apache module)
#
# Required Buan configuration:
# [app.command.parameter] = 'do' (see below)
# [app.command.urlPrefix] = '' (ie. empty string)
#
# You can actually use any custom value for [app.command.parameter], as long as
# you replace "do" in the directives below with your custom parameter.
#
<IfModule mod_rewrite.c>
    Options +FollowSymLinks
    IndexIgnore /*
    RewriteEngine On
    RewriteBase /

    # Uncomment and adjust these lines if you have installed the application
    # in a subfolder of your document root
    #RewriteCond %{REQUEST_FILENAME} !-f
    #RewriteCond %{REQUEST_FILENAME} !-d
    #RewriteCond %{REQUEST_FILENAME} buan/buan\-pub
    #RewriteRule ^buan/buan\-pub(.*)$ path/to/subfolder/containing/buan/buan-pub$1 [L]

    # Handle all other requests
    RewriteCond %{REQUEST_FILENAME} !index.php
    RewriteCond %{REQUEST_FILENAME} !favicon.ico
    RewriteCond %{REQUEST_FILENAME} !robots.txt
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteRule ^(.*)$ index.php?do=$1 [QSA,L]
</IfModule>

```

```
</IfModule>
```

```
# Fallback
```

```
# This method will be used if you do not have the "mod_rewrite" Apache module  
# available on the server.
```

```
#
```

```
# Required Buan configuration:
```

```
# [app, command, parameter] = 'do' (see below)
```

```
# [app, command, urlPrefix] = 'do' (see below)
```

```
#
```

```
# You can actually use any custom values for above configuration variables, as  
# long as you replace "do" in the directives below with your custom parameter  
# and change the name of the "do" file in this folder accordingly.
```

```
#
```

```
<IfModule !mod_rewrite.c>
```

```
  <Files "do">
```

```
    ForceType application/x-httpd-php
```

```
  </Files>
```

```
</IfModule>
```