

```
# Use UTF-8 encoding for anything served text/plain or text/html
```

```
AddDefaultCharset utf-8
```

```
# Force UTF-8 for a number of file formats
```

```
AddCharset utf-8 .html .css .js .xml .json .rss .atom
```

```
# Allow access from all domains for webfonts.
```

```
# Alternatively you could only whitelist your
```

```
# subdomains like "subdomain.example.com".
```

```
<FilesMatch "\.(ttf|ttdl|otf|eot|woff|font. css)$">
```

```
  <IfModule mod_headers.c>
```

```
    Header set Access-Control-Allow-Origin "*"
```

```
  </IfModule>
```

```
</FilesMatch>
```

```
# JavaScript
```

```
# Normalize to standard type (it's sniffed in IE anyways)
```

```
# tools.ietf.org/html/rfc4329#section-7.2
```

```
AddType application/javascript js
```

```
# SVG.
```

```
# Required for svg webfonts on iPad
```

```
# twitter.com/FontSquirrel/status/14855840545
```

```
AddType image/svg+xml svg svgz
```

```
AddEncoding gzip svgz
```

```
# Webfonts
```

```
AddType application/vnd.ms-fontobject eot
```

```
AddType application/x-font-ttf ttf ttc
```

```
AddType font/opentype otf
```

```
AddType application/x-font-woff woff
```

```
# Assorted types
```

```
AddType image/x-icon ico
```

```
AddType image/webp webp
```

```
AddType text/cache-manifest appcache manifest
```

```
AddType text/x-component htc
```

```
AddType application/x-chrome-extension crx
```

```
AddType application/x-xpinstall xpi
```

```
AddType application/octet-stream safariextz
```