

```
# A .htaccess file is a hidden file which runs on Unix servers  
# and provides directives. Renaming this file to .htaccess and  
# placing in your root directory _should_ enable GZip compression,  
# reducing the weight of pages/scripts being served.
```

```
# Please note that all of these rules are optimizations  
# and not necessary for jQuery to work. If this causes  
# any issues with your server, just remove.
```

```
<ifModule mod_gzip.c>  
  mod_gzip_on Yes  
  mod_gzip_dechunk Yes  
  mod_gzip_item_include file \.(html?|txt|css|js|php|pl)$  
  mod_gzip_item_include handler ^cgi-script$  
  mod_gzip_item_include mime ^text/. *  
  mod_gzip_item_include mime ^application/x-javascript.*  
  mod_gzip_item_exclude mime ^image/. *  
  mod_gzip_item_exclude rspheader ^Content-Encoding:.*gzip.*  
</ifModule>
```

```
<ifModule mod_deflate.c>  
  AddOutputFilterByType DEFLATE text/html text/plain text/xml text/css text/javascript  
  application/x-javascript  
</ifModule>
```

```
<ifModule mod_expires.c>  
  ExpiresActive On  
  ExpiresDefault "access plus 1 seconds"  
  ExpiresByType text/html "access plus 1 seconds"  
  ExpiresByType image/gif "access plus 2592000 seconds"  
  ExpiresByType image/jpeg "access plus 2592000 seconds"  
  ExpiresByType image/png "access plus 2592000 seconds"  
  ExpiresByType text/css "access plus 604800 seconds"  
  ExpiresByType text/javascript "access plus 216000 seconds"  
  ExpiresByType application/x-javascript "access plus 216000 seconds"  
</ifModule>
```

```
<ifModule mod_headers.c>  
  Header unset ETag  
</ifModule>
```

FileETag None

```
<ifModule mod_headers.c>
```

```
  Header unset Last-Modified
```

```
</ifModule>
```

```
AddType text/cache-manifest .manifest
```