

RewriteEngine on

*# Some hosts require a rewritebase rule, if so, uncomment the RewriteBase line below. If you are running from a subdirectory, your rewritebase should match the name of the path to where stacey is stored.*

*# ie. if in a folder named 'stacey', RewriteBase /stacey*

*#RewriteBase /*

ErrorDocument 404 /404.html

*# Rewrite any calls to \*.html, \*.json, \*.xml, \*.atom, \*.rss, \*.rdf or \*.txt if a folder matching \* exists*

RewriteCond %{REQUEST\_FILENAME} !-f

RewriteCond %{REQUEST\_URI} !public/

RewriteCond %{DOCUMENT\_ROOT}/public/\$1.\$2 !-f

RewriteRule (.+)\.(html|json|xml|atom|rss|rdf|txt)\$ \$1/ [L]

*# Add a trailing slash to directories*

RewriteCond %{REQUEST\_FILENAME} !-f

RewriteCond %{REQUEST\_FILENAME} !-d

RewriteCond %{REQUEST\_URI} !(\.|\/)?

RewriteCond %{REQUEST\_URI} !(.\*)/\$

RewriteRule ([^/]+)\$ \$1/ [L]

*# Rewrite any calls to /render to the image parser*

RewriteCond %{REQUEST\_URI} render/

RewriteRule ^render/. app/parsers/slr/ [L]

*# Rewrite any calls to /\* or /app to the index.php file*

RewriteCond %{REQUEST\_URI} /app/\$

RewriteRule ^app/ index.php [L]

RewriteCond %{REQUEST\_FILENAME} !-f

RewriteCond %{REQUEST\_FILENAME} !-d

RewriteRule ^(.\*)/\$ index.php?/\$1/ [L,QSA]

*# Rewrite any file calls to the public directory*

RewriteCond %{REQUEST\_FILENAME} !-f

RewriteCond %{REQUEST\_FILENAME} !-d

RewriteCond %{REQUEST\_URI} !public/

RewriteRule ^(.+)\$ public/\$1 [L]

```
# Allow basic authentication
RewriteRule .* - [E=HTTP_AUTHORIZATION:%{HTTP:Authorization}]

# Prevent access to .txt files
<Files ~ "\.txt$">
    Order allow,deny
    Deny from all
</Files>

# Increase cookie security
<IfModule php5_module>
    php_value session.cookie_httponly true
</IfModule>
```