

```
#
# Apache/PHP/Drupal settings:
#
## MIME TYPES ###
AddType video/x-flv .flv
AddType application/x-shockwave-flash .swf
AddType image/x-icon .ico
<ifModule mod_deflate.c>
Addtype font/opentype .otf
Addtype font/eot .eot
Addtype font/truetype .ttf
AddOutputFilterByType DEFLATE text/html text/plain text/xml application/xml
application/xhtml+xml text/css text/javascript application/javascript application/x-
javascript font/opentype font/truetype font/eot
</ifModule>
# BEGIN Expire headers
<IfModule mod_expires.c>
ExpiresActive On
ExpiresByType font/ttf "access plus 10 years"
ExpiresByType font/otf "access plus 10 years"
ExpiresByType image/jpg "access 1 year"
ExpiresByType image/jpeg "access 1 year"
ExpiresByType image/gif "access 1 year"
ExpiresByType image/png "access 1 year"
ExpiresByType text/css "access 1 month"
ExpiresByType application/pdf "access 1 month"
ExpiresByType text/javascript "access plus 216000 seconds"
ExpiresByType text/x-javascript "access 1 month"
ExpiresByType application/x-shockwave-flash "access 1 month"
ExpiresByType image/x-icon "access 1 year"
ExpiresByType text/html "access plus 600 seconds"
ExpiresByType application/xhtml+xml "access plus 600 seconds"
ExpiresDefault "access 2 days"
</IfModule>
# END Expire headers
# BEGIN Cache-Control Headers
<ifModule mod_headers.c>
<FilesMatch "\.(ico|pdf|flv|jpe?g|png|gif|jst|css|swf)$">
    ExpiresActive On
    ExpiresDefault "access plus 1 year"
</FilesMatch>
```

```

</filesMatch>
  <filesMatch "\.(ico|jpe?g|png|gif|swf)$">
    Header set Cache-Control "public"
  </filesMatch>
  <filesMatch "\.(css)$">
    Header set Cache-Control "public"
  </filesMatch>
  <filesMatch "\.(js)$">
    Header set Cache-Control "private"
  </filesMatch>
  <filesMatch "\.(x?html?|php)$">
    Header set Cache-Control "private, must-revalidate"
  </filesMatch>
</ifModule>
# END Cache-Control Headers
# BEGIN Turn ETags Off
FileETag None
# END Turn ETags Off
# Protect files and directories from prying eyes.
<FilesMatch "\.(engine|incl|info|install|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?
|xtmpl|svn-base)$|^(\code-style\.|Entries.*|Repository|Root|Tag|Template|all-
wcprops|entries|format)$">
  Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
# For security reasons, Option followsymlinks cannot be overridden.
#Options +FollowSymLinks
Options +SymLinksIfOwnerMatch

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
  ErrorDocument 404 "The requested file favicon.ico was not found."
</Files>

```

```
# Set the default handler.
```

```
DirectoryIndex index.php
```

```
# Override PHP settings. More in sites/default/settings.php
```

```
# but the following cannot be changed at runtime.
```

```
# PHP 4, Apache 1.
```

```
<IfModule mod_php4.c>
```

```
  php_value magic_quotes_gpc          0
  php_value register_globals          0
  php_value session.auto_start       0
  php_value mbstring.http_input      pass
  php_value mbstring.http_output     pass
  php_value mbstring.encoding_translation 0
```

```
</IfModule>
```

```
# PHP 4, Apache 2.
```

```
<IfModule sapi_apache2.c>
```

```
  php_value magic_quotes_gpc          0
  php_value register_globals          0
  php_value session.auto_start       0
  php_value mbstring.http_input      pass
  php_value mbstring.http_output     pass
  php_value mbstring.encoding_translation 0
```

```
</IfModule>
```

```
# PHP 5, Apache 1 and 2.
```

```
<IfModule mod_php5.c>
```

```
  php_value magic_quotes_gpc          0
  php_value register_globals          0
  php_value session.auto_start       0
  php_value mbstring.http_input      pass
  php_value mbstring.http_output     pass
  php_value mbstring.encoding_translation 0
```

```
</IfModule>
```

```
# Requires mod_expires to be enabled.
```

```
<IfModule mod_expires.c>
```

```
  # Enable expirations.
```

```
  ExpiresActive On
```

```
  # Cache all files for 2 weeks after access (A).
```

```

ExpiresDefault A1209600
# Do not cache dynamically generated pages.
ExpiresByType text/html A1
</IfModule>

# Various rewrite rules.
<IfModule mod_rewrite.c>
RewriteEngine on

# If your site can be accessed both with and without the 'www.' prefix, you
# can use one of the following settings to redirect users to your preferred
# URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
#
# To redirect all users to access the site WITH the 'www.' prefix,
# (http://example.com/... will be redirected to http://www.example.com/...)
# adapt and uncomment the following:
# RewriteCond %{HTTP_HOST} ^example\.com$ [NC]
# RewriteRule ^(.*)$ http://www.example.com/$1 [L,R=301]
#
# To redirect all users to access the site WITHOUT the 'www.' prefix,
# (http://www.example.com/... will be redirected to http://example.com/...)
# uncomment and adapt the following:
# RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]
# RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]

# Modify the RewriteBase if you are using Drupal in a subdirectory or in a
# VirtualDocumentRoot and the rewrite rules are not working properly.
# For example if your site is at http://example.com/drupal uncomment and
# modify the following line:
# RewriteBase /drupal
#
# If your site is running in a VirtualDocumentRoot at http://example.com/,
# uncomment the following line:
# RewriteBase /

# Rewrite old-style URLs of the form 'node.php?id=x'.
#RewriteCond %{REQUEST_FILENAME} !-f
#RewriteCond %{REQUEST_FILENAME} !-d
#RewriteCond %{QUERY_STRING} ^id=([^\%]+)$
#RewriteRule node.php index.php?q=node/view/%1 [L]

```

```
# Rewrite old-style URLs of the form 'module.php?mod=x'.
#RewriteCond %{REQUEST_FILENAME} !-f
#RewriteCond %{REQUEST_FILENAME} !-d
#RewriteCond %{QUERY_STRING} ^mod=([^&]+)$
#RewriteRule module.php index.php?q=%1 [L]

# Rewrite current-style URLs of the form 'x' to the form 'index.php?q=x'.
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} !=/favicon.ico
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
</IfModule>

# $Id: .htaccess,v 1.81.2.6 2009/02/26 07:03:29 drumm Exp $
```