

```
#  
# Apache/PHP/Drupal settings:  
#  
  
# Protect files and directories from prying eyes.  
<FilesMatch "\.(engine|incl|info|install|module|profile|test|pol|sh|.*sql|themel|tpl)\(\.php\)?  
|xtmpl|svn-base)\$|^(code-style|\.|pl|Entries|.*|Repository|Root|Tag|Template|all-  
wpprops|entries|format)\$">  
    Order allow,deny  
</FilesMatch>  
  
# Don't show directory listings for URLs which map to a directory.  
Options -Indexes  
  
# Follow symbolic links in this directory.  
Options +FollowSymLinks  
  
# Make Drupal handle any 404 errors.  
ErrorDocument 404 /index.php  
  
# Force simple error message for requests for non-existent favicon.ico.  
<Files favicon.ico>  
    # There is no end quote below, for compatibility with Apache 1.3.  
    ErrorDocument 404 "The requested file favicon.ico was not found."  
</Files>  
  
# Set the default handler.  
DirectoryIndex index.php  
  
# Override PHP settings. More in sites/default/settings.php  
# but the following cannot be changed at runtime.  
  
# PHP 4, Apache 1.  
<IfModule mod_php4.c>  
    php_value magic_quotes_gpc          0  
    php_value register_globals         0  
    php_value session.auto_start      0  
    php_value mbstring.http_input     pass  
    php_value mbstring.http_output    pass  
    php_value mbstring.encoding_translation 0  
</IfModule>
```

```
</IfModule>

# PHP 4, Apache 2.
<IfModule sapi_apache2.c>
    php_value magic_quotes_gpc          0
    php_value register_globals          0
    php_value session.auto_start       0
    php_value mbstring.http_input      pass
    php_value mbstring.http_output     pass
    php_value mbstring.encoding_translation 0
</IfModule>

# PHP 5, Apache 1 and 2.
<IfModule mod_php5.c>
    php_value magic_quotes_gpc          0
    php_value register_globals          0
    php_value session.auto_start       0
    php_value mbstring.http_input      pass
    php_value mbstring.http_output     pass
    php_value mbstring.encoding_translation 0
</IfModule>

# Requires mod_expires to be enabled.
<IfModule mod_expires.c>
    # Enable expirations.
    ExpiresActive On

    # Cache all files for 2 weeks after access (A).
    ExpiresDefault A1209600

<FileMatch \.php$>
    # Do not allow PHP scripts to be cached unless they explicitly send cache
    # headers themselves. Otherwise all scripts would have to overwrite the
    # headers set by mod_expires if they want another caching behavior. This may
    # fail if an error occurs early in the bootstrap process, and it may cause
    # problems if a non-Drupal PHP file is installed in a subdirectory.
    ExpiresActive Off
</FileMatch>
</IfModule>

# Various rewrite rules.
...  
...
```

```
<IfModule mod_rewrite.c>
    RewriteEngine on

    # If your site can be accessed both with and without the 'www.' prefix, you
    # can use one of the following settings to redirect users to your preferred
    # URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
    #

    # To redirect all users to access the site WITH the 'www.' prefix,
    # (http://example.com/...) will be redirected to http://www.example.com/...)
    # adapt and uncomment the following:
    # RewriteCond %{HTTP_HOST} ^example\.com$ [NC]
    # RewriteRule ^(.*)$ http://www.example.com/$1 [L,R=301]
    #

    # To redirect all users to access the site WITHOUT the 'www.' prefix,
    # (http://www.example.com/...) will be redirected to http://example.com/...)
    # uncomment and adapt the following:
    # RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]
    # RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]

    # Modify the RewriteBase if you are using Drupal in a subdirectory or in a
    # VirtualDocumentRoot and the rewrite rules are not working properly.
    # For example if your site is at http://example.com/drupal uncomment and
    # modify the following line:
    # RewriteBase /drupal
    #

    # If your site is running in a VirtualDocumentRoot at http://example.com/,
    # uncomment the following line:
    # RewriteBase /

    # Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteCond %{REQUEST_URI} !=/favicon.ico
    RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
</IfModule>

# $Id: .htaccess,v 1.90.2.4 2009/12/07 12:00:40 goba Exp $
```