

```
#####
## overrides deployment configuration mode value
## use command bin/magento deploy:mode:set to switch modes

# SetEnv MAGE_MODE developer

#####
## uncomment these lines for CGI mode
## make sure to specify the correct cgi php binary file name
## it might be /cgi-bin/php-cgi

# Action php5-cgi /cgi-bin/php5-cgi
# AddHandler php5-cgi .php

#####
## GoDaddy specific options

# Options -MultiViews

## you might also need to add this line to php.ini
## cgi.fix_pathinfo = 1
## if it still doesn't work, rename php.ini to php5.ini

#####
## this line is specific for 1and1 hosting

    #AddType x-mapp-php5 .php
    #AddHandler x-mapp-php5 .php

#####
## default index file

    DirectoryIndex index.php

<IfModule mod_php5.c>

#####
## adjust memory limit

    php_value memory_limit 768M
    php_value max_execution_time 18000
```

```
php_value max_execution_time 10000
```

```
#####
```

```
## disable automatic session start  
## before autoloader was initialized
```

```
php_flag session.auto_start off
```

```
#####
```

```
## enable resulting html compression
```

```
php_flag zlib.output_compression on
```

```
#####
```

```
## disable user agent verification to not break multiple image upload
```

```
php_flag suhosin.session.cryptua off
```

```
</IfModule>
```

```
<IfModule mod_php7.c>
```

```
#####
```

```
## adjust memory limit
```

```
php_value memory_limit 768M
```

```
php_value max_execution_time 18000
```

```
#####
```

```
## disable automatic session start  
## before autoloader was initialized
```

```
php_flag session.auto_start off
```

```
#####
```

```
## enable resulting html compression
```

```
php_flag zlib.output_compression on
```

```
#####
```

```
## disable user agent verification to not break multiple image upload
```

```
php_flag suhosin.session.cryptua off
```

```
</IfModule>
```

```
<IfModule mod_security.c>
```

```
#####
```

```
## disable POST processing to not break multiple image upload
```

```
SecFilterEngine Off
```

```
SecFilterScanPOST Off
```

```
</IfModule>
```

```
<IfModule mod_deflate.c>
```

```
#####
```

```
## enable apache served files compression
```

```
## http://developer.yahoo.com/performance/rules.html#gzip
```

```
# Insert filter on all content
```

```
###SetOutputFilter DEFLATE
```

```
# Insert filter on selected content types only
```

```
#AddOutputFilterByType DEFLATE text/html text/plain text/xml text/css text/javascript
```

```
# Netscape 4.x has some problems...
```

```
#BrowserMatch ^Mozilla/4 gzip-only-text/html
```

```
# Netscape 4.06-4.08 have some more problems
```

```
#BrowserMatch ^Mozilla/4\.[0678] no-gzip
```

```
# MSIE masquerades as Netscape, but it is fine
```

```
#BrowserMatch \bMSIE !no-gzip !gzip-only-text/html
```

```
# Don't compress images
```

```
#SetEnvIfNoCase Request_URI \.(?:gif|jpe?g|png)$ no-gzip dont-vary
```

```
# Make sure proxies don't deliver the wrong content
```

```
#Header append Vary User-Agent env=!dont-vary
```

```
</IfModule>
```

```
<IfModule mod_ssl.c>
```

```
#####  
## make HTTPS env vars available for CGI mode
```

```
    SSLOptions StdEnvVars
```

```
</IfModule>
```

```
#####  
## workaround for Apache 2.4.6 CentOS build when working via ProxyPassMatch with HHVM (or  
any other)  
## Please, set it on virtual host configuration level
```

```
##    SetEnvIf Authorization "(.*)" HTTP_AUTHORIZATION=$1  
#####
```

```
<IfModule mod_rewrite.c>
```

```
#####  
## enable rewrites
```

```
    Options +FollowSymLinks  
    RewriteEngine on
```

```
#####  
## you can put here your magento root folder  
## path relative to web root
```

```
    #RewriteBase /magento/
```

```
#####  
## workaround for HTTP authorization  
## in CGI environment
```

```
    RewriteRule .* - [E=HTTP_AUTHORIZATION:%{HTTP:Authorization}]
```

```
#####  
## TRACE and TRACK HTTP methods disabled to prevent XSS attacks
```

```
    RewriteCond %{REQUEST_METHOD} ^TRAC[EK]
```

```
RewriteRule .* - [L,R=405]
```

```
#####
```

```
## redirect for mobile user agents
```

```
#RewriteCond %{REQUEST_URI} !^/mobiledirectoryhere/.*$
```

```
#RewriteCond %{HTTP_USER_AGENT} "android|blackberry|ipad|iphone|ipod|iemo|opera  
mobile|palmos|webos|googlebot-mobile" [NC]
```

```
#RewriteRule ^(.*)$ /mobiledirectoryhere/ [L,R=302]
```

```
#####
```

```
## never rewrite for existing files, directories and links
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_FILENAME} !-l
```

```
#####
```

```
## rewrite everything else to index.php
```

```
RewriteRule .* index.php [L]
```

```
</IfModule>
```

```
#####
```

```
## Prevent character encoding issues from server overrides  
## If you still have problems, use the second line instead
```

```
AddDefaultCharset Off
```

```
#AddDefaultCharset UTF-8
```

```
<IfModule mod_expires.c>
```

```
#####
```

```
## Add default Expires header  
## http://developer.yahoo.com/performance/rules.html#expires
```

```
ExpiresDefault "access plus 1 year"
```

```
ExpiresByType text/html A0
```

```
ExpiresByType text/plain A0
```

```
</IfModule>
```

```
#####
```

```
## Deny access to root files to hide sensitive application information
```

```
RedirectMatch 404 /\.git
```

```
<Files composer.json>
```

```
order allow,deny
```

```
deny from all
```

```
</Files>
```

```
<Files composer.lock>
```

```
order allow,deny
```

```
deny from all
```

```
</Files>
```

```
<Files .gitignore>
```

```
order allow,deny
```

```
deny from all
```

```
</Files>
```

```
<Files .htaccess>
```

```
order allow,deny
```

```
deny from all
```

```
</Files>
```

```
<Files .htaccess.sample>
```

```
order allow,deny
```

```
deny from all
```

```
</Files>
```

```
<Files .php_cs>
```

```
order allow,deny
```

```
deny from all
```

```
</Files>
```

```
<Files .travis.yml>
```

```
order allow,deny
```

```
deny from all
```

```
</Files>
```

```
<Files CHANGELOG.md>
```

```
order allow,deny
```

```
deny from all
```

```
</Files>
```

```
<Files CONTRIBUTING.md>
```

```
order allow,deny
```

```
deny from all
```

```
</Files>
<Files CONTRIBUTOR_LICENSE_AGREEMENT.html>
    order allow,deny
    deny from all
</Files>
<Files COPYING.txt>
    order allow,deny
    deny from all
</Files>
<Files Gruntfile.js>
    order allow,deny
    deny from all
</Files>
<Files LICENSE.txt>
    order allow,deny
    deny from all
</Files>
<Files LICENSE_AFL.txt>
    order allow,deny
    deny from all
</Files>
<Files nginx.conf.sample>
    order allow,deny
    deny from all
</Files>
<Files package.json>
    order allow,deny
    deny from all
</Files>
<Files php.ini.sample>
    order allow,deny
    deny from all
</Files>
<Files README.md>
    order allow,deny
    deny from all
</Files>
```

```
#####
```

```
## If running in cluster environment, uncomment this
```

```
## http://developer.yahoo.com/performance/rules.html#etags
```

```
#FileETag none
```

```
#####
```

```
## Add custom headers
```

```
<IfModule mod_headers.c>
```

```
    Header set X-Content-Type-Options "nosniff"
```

```
    Header set X-XSS-Protection "1; mode=block"
```

```
</IfModule>
```