

```

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    BrowserMatch MSIE ie
    Header set X-UA-Compatible "IE=Edge,chrome=1" env=ie
  </IfModule>
</IfModule>

<IfModule mod_headers.c>
  Header append Vary User-Agent
</IfModule>

<FilesMatch "\.(ttf|otf|eot|woff|font.css)$">
  <IfModule mod_headers.c>
    Header set Access-Control-Allow-Origin "*"
  </IfModule>
</FilesMatch>

<filesMatch "\.(html|htm)$">
  FileETag None
  <ifModule mod_headers.c>
    Header unset ETag
    Header set Cache-Control "max-age=0, no-cache, no-store, must-revalidate"
    Header set Pragma "no-cache"
    Header set Expires "Wed, 11 Jan 1984 05:00:00 GMT"
  </ifModule>
</filesMatch>

# GZip compression
<IfModule mod_deflate.c>
  # force deflate for mangled headers developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-
  beyond-gzipping/
  <IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
      SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
      ^((gzip|deflate)\s,?\s(gzip|deflate)?|X(4,13)|^(4,13)|-(4,13))$ HAVE_Accept-Encoding
      RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
    </IfModule>
  </IfModule>
  # html, txt, css, js, json, xml, htc:
  <IfModule filter_module>
    FilterDeflate on
    FilterCompression COMPRESS

```

```

    FilterDeclare    COMPRESS
    FilterProvider   COMPRESS  DEFLATE resp=Content-Type
/text/(html|css|javascript|plain|x(ml|-component))/
    FilterProvider   COMPRESS  DEFLATE resp=Content-Type
/application/(javascript|json|xml|x-javascript)/
    FilterChain      COMPRESS
    FilterProtocol    COMPRESS  change=yes;byteranges=no
</IfModule>

<IfModule !mod_filter.c>
    # Legacy versions of Apache
    AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
    AddOutputFilterByType DEFLATE text/javascript application/javascript application/x-
javascript
    AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
</IfModule>

<FilesMatch "\.(ttf|otf|eot|svg)$" >
    SetOutputFilter DEFLATE
</FilesMatch>
</IfModule>

<IfModule mod_expires.c>
    ExpiresActive on

    # Perhaps better to whitelist expires rules? Perhaps.
    ExpiresDefault          "access plus 1 month"

    # cache, appcache needs re-requests in FF 3.6 (thx Remy "Introducing HTML5")
    ExpiresByType text/cache-manifest "access plus 0 seconds"

    # your document html
    ExpiresByType text/html "access plus 0 seconds"

    # data
    ExpiresByType text/xml "access plus 0 seconds"
    ExpiresByType application/xml "access plus 0 seconds"
    ExpiresByType application/json "access plus 0 seconds"

    # rss feed
    ExpiresByType application/rss+xml "access plus 1 hour"

```

```
# favicon (cannot be renamed)
ExpiresByType image/x-icon "access plus 1 week"

# media: images, video, audio
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/jpg "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# htc files (css3pie)
ExpiresByType text/x-component "access plus 1 month"

# webfonts
ExpiresByType font/truetype "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# css and javascript
ExpiresByType text/css "modification plus 1 month"
ExpiresByType application/javascript "modification plus 2 months"
ExpiresByType text/javascript "modification plus 2 months"

<IfModule mod_headers.c>
  Header append Cache-Control "public"
</IfModule>

</IfModule>

# Since we're sending far-future expires, we don't need ETags for
# static content.
FileETag None

<filesMatch "\.(html|htm)$">
  FileETag None
```

```
<ifModule mod_headers.c>
  Header unset ETag
  Header set Cache-Control "max-age=0, no-cache, no-store, must-revalidate"
  Header set Pragma "no-cache"
  Header set Expires "Wed, 11 Jan 1984 05:00:00 GMT"
</ifModule>
</filesMatch>

# Use utf-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force utf-8 for a number of file formats
AddCharset utf-8 .html .css .js .xml .json .rss

# We don't need to tell everyone we're apache.
ServerSignature Off

<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /
RewriteRule ^index\.php$ - [L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /index.php [L]
</IfModule>

<Files ".env">
  Order allow,deny
  Deny from all
</Files>
```