


```

RewriteCond %{QUERY_STRING} http:// [NC,OR]
RewriteCond %{QUERY_STRING} https:// [NC,OR]
RewriteCond %{QUERY_STRING} \=|\ | [NC,OR]
RewriteCond %{QUERY_STRING} ^(\. *)\/self\/(\. *)$ [NC,OR]
RewriteCond %{QUERY_STRING} ^(\. *)cPath=http://(\. *)$ [NC,OR]
RewriteCond %{QUERY_SCRIPT} (\<|%)\. *script\. *(\>|%) [NC,OR]
RewriteCond %{QUERY_SCRIPT} (<|%)%3C([\^s]*s)+cript\. *(>|%) [NC,OR]
RewriteCond %{QUERY_SCRIPT} (\<|%)\. *iframe\. *(\>|%) [NC,OR]
RewriteCond %{QUERY_SCRIPT} (<|%)%3C([\^i]*i)+frame\. *(>|%) [NC,OR]
RewriteCond %{QUERY_STRING} base64_encode.*\(\. *) [NC,OR]
RewriteCond %{QUERY_STRING} base64_(en|de)code[^\(\. *)$ [NC,OR]
RewriteCond %{QUERY_STRING} GLOBALS(=| \[| \]| \[0-9A-Z]{0,2}) [OR]
RewriteCond %{QUERY_STRING} _REQUEST(=| \[| \]| \[0-9A-Z]{0,2}) [OR]
RewriteCond %{QUERY_STRING} ^.*\(|\)|\(|\)|\<|>.* [NC,OR]
RewriteCond %{QUERY_STRING} (NULL|OUTFILE|LOAD_FILE) [OR]
RewriteCond %{QUERY_STRING} (\. /| \. . /| \. . . /)+(\. motd|etc|bin) [NC,OR]
RewriteCond %{QUERY_STRING} (localhost|loopback|127\.\. 0\.\. 0\.\. 1) [NC,OR]
RewriteCond %{QUERY_STRING} (<|>|'|"%0A%0D%27%3C%3E%00) [NC,OR]
RewriteCond %{QUERY_STRING} concat[^\(\. *)$ [NC,OR]
RewriteCond %{QUERY_STRING} union([\^s]*s)+select [NC,OR]
RewriteCond %{QUERY_STRING} union([\^a]*a)+11([\^s]*s)+select [NC,OR]
RewriteCond %{QUERY_STRING} (;|<|>|'|"| \)|"%0A%0D%22%27%3C%3E%00).*
(</\*| union| select| insert| drop| delete| update| cast| create| char| convert| alter| declare| order| scr
RewriteCond %{QUERY_STRING} (sp_executesql) [NC]
RewriteRule ^(\. *)$ - [F,L]

RewriteCond %{REMOTE_ADDR} !^88\.\. 55\.\. 66\.\. 200$
RewriteCond %{REQUEST_URI} !^/bp-maintenance\. php$
RewriteCond %{REQUEST_URI} !^/wp-content/plugins/bulletproof-security/abstract-blue-bg\. png$
RewriteRule ^(\. *)$ /bp-maintenance. php [L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /index. php [L]

```