

```
# Apache .htaccess for PukiWiki
#
# $Id: .htaccess,v 1.14.2 2006/08/06 23:25:00 upk Exp $
# Copyright (C)
# 2006      PukiWiki Plus! Developers Team
# 2002-2005 PukiWiki Developers Team
# 2001      Originally written by yu-ji
# License: GPL v2 or (at your option) any later version
#
# NOTE: Correct permission of this file 644(or 604)

## Access control by Order/Allow/Deny directives
## needs 'AllowOverride Limit' at httpd.conf

# Prohibit direct access to .htaccess, .htpasswd or others
# (If it's not set by default)
# <FilesMatch "^\.ht">
#   Order allow,deny
#   Deny from all
# </FilesMatch>

ErrorDocument 404 /error/404.html
# SetEnv TZ JST-9

AddDefaultCharset UTF-8
AddType "text/html; charset=UTF-8" .html

AddType application/x-java-jnlp-file .jnlp
AddType application/x-java-archive-diff .jardiff
AddType application/java-archive .jar
# Addtype application/pdf .pdf

#Options All -Indexes
#IndexOptions Charset=UTF-8
DirectoryIndex index.php FrontPage.html index.html

<Files robots.txt>
order deny,allow
allow from all
</Files>
```

```
# Prohibit direct access
<FilesMatch "\.(ini\.php|ling\.php)$">
    Order allow,deny
    Deny from all
</FilesMatch>

## Authentication to this directory with basic-auth
## needs 'AllowOverride AuthConfig' at httpd.conf
#AuthType Basic
#AuthName "Authentication required"
#AuthUserFile /path/to/.htpasswd
#AuthGroupFile /dev/null
#Require valid-user

#AuthType Digest
#AuthName "PukiWikiAuth"
#AuthDigestProvider file
#AuthUserFile /path/to/.htdigest
#Require valid-user
#BrowserMatch "MSIE" AuthDigestEnableQueryStringHack=On

## Using zlib.output_compression per directory (via .htaccess)
## needs 'AllowOverride Options' at httpd.conf
##
## NOTE:
## Define PKWK_ZLIB_LOADABLE_MODULE somewhere if you are using
## PHP extension as loadable module (especially FreeBSD ports)
## (See BugTrack/738 for detail)
#php_flag zlib.output_compression On

RewriteEngine on
RewriteBase /

# RewriteCond %{REQUEST_URI} ^/(en|PukiWiki|swing/swing[ ^a-z]).*$
# RewriteRule .* - [G]

# RewriteRule ^Recent\.html$ index.php?cmd=recent [L]
# RewriteRule ^List\.html$ index.php?cmd=list [L]
RewriteRule ^sitemap\.xml$ index.php?cmd=sitemaps [QSA,PT,L]
RewriteRule ^swing-sitemap\.xml$ index.php?cmd=sitemaps&category=Swing [QSA,PT,L]
```

```
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteCond %(REQUEST_URI) !/\.(html)$
RewriteRule ^(.+)\.(html)$ index.php?cmd=read&page=$1 [QSA,PT,L]
```

```
<FilesMatch "\.(js|css|xml|gz)$">
Header append Vary: Accept-Encoding
</FilesMatch>
```

```
<FilesMatch "\.(js|css)$">
RewriteEngine on
RewriteBase /
RewriteCond %(HTTP:Accept-Encoding) gzip
RewriteCond %(REQUEST_FILENAME) !\.(gz)$
RewriteCond %(REQUEST_FILENAME)\.(gz) -s
RewriteRule ^.+ $(%{REQUEST_URI}).gz
</FilesMatch>
```

```
<files *.js.gz>
AddType "text/javascript; charset=UTF-8" .gz
</files>
<files *.css.gz>
AddType "text/css" .gz
</files>
AddEncoding x-gzip .gz
```

```
<FilesMatch "\.(ico|jpg|jpeg|png|gif|js|css|gz|woff)$">
FileETag none
Header set Cache-Control "max-age=2419200, public"
</FilesMatch>
```