

Options +FollowSymlinks -Indexes

AddDefaultCharset UTF-8

```
# #####  
# # INTERNET EXPLORER #  
# #####
```

```
# -----  
# | Better website experience |  
# -----
```

```
# Force IE to render pages in the highest available mode in the various  
# cases when it may not: http://hsivonen.iki.fi/doctype/ie-mode.pdf.  
# Use, if installed, Google Chrome Frame.
```

```
<IfModule mod_headers.c>  
  Header set X-UA-Compatible "IE=edge,chrome=1"  
  <FilesMatch "\.(appcache|crx|css|eot|gif|htc|ico|jpe?  
gl|jsl|m4a|m4v|manifest|mp4|oex|ogal|oggl|ogv|otf|pdf|png|safariextz|svg|svgz|ttf|vcf|webapp|wet  
  Header unset X-UA-Compatible  
  </FilesMatch>  
</IfModule>
```

```
# #####  
# # MIME TYPES AND ENCODING #  
# #####
```

```
# -----  
# | Proper MIME types for all files |  
# -----
```

```
<IfModule mod_mime.c>
```

```
# Audio  
AddType audio/mp4 m4a f4a f4b  
AddType audio/ogg oga ogg
```

```
# JavaScript  
# Normalize to standard type (it's sniffed in IE anyways):  
# ###
```

```
# http://tools.ietf.org/html/rfc4329#section-7.2
```

```
AddType application/javascript js jsonp
```

```
AddType application/json json
```

Video

```
AddType video/mp4 mp4 m4v f4v f4p
```

```
AddType video/ogg ogv
```

```
AddType video/webm webm
```

```
AddType video/x-flv flv
```

Web fonts

```
AddType application/font-woff woff
```

```
AddType application/vnd.ms-fontobject eot
```

```
# Browsers usually ignore the font MIME types and sniff the content,  
# however, Chrome shows a warning if other MIME types are used for the  
# following fonts.
```

```
AddType application/x-font-ttf ttc ttf
```

```
AddType font/opentype otf
```

```
# Make SVGZ fonts work on iPad:
```

```
# https://twitter.com/FontSquirrel/status/14855840545
```

```
AddType image/svg+xml svg svgz
```

```
AddEncoding gzip svgz
```

Other

```
AddType application/octet-stream safariextz
```

```
AddType application/x-chrome-extension crx
```

```
AddType application/x-opera-extension oex
```

```
AddType application/x-shockwave-flash swf
```

```
AddType application/x-web-app-manifest+json webapp
```

```
AddType application/x-xpinstall xpi
```

```
AddType application/xml atom rdf rss xml
```

```
AddType image/webp webp
```

```
AddType image/x-icon ico
```

```
AddType text/cache-manifest appcache manifest
```

```
AddType text/vtt vtt
```

```
AddType text/x-component htc
```

```
AddType text/x-vcard vcf
```

```
</IfModule>
```

```

# -----
# | UTF-8 encoding |
# -----

# Use UTF-8 encoding for anything served as `text/html` or `text/plain`.
AddDefaultCharset utf-8

# Force UTF-8 for certain file formats.
<IfModule mod_mime.c>
    AddCharset utf-8 .atom .css .js .json .rss .vtt .webapp .xml
</IfModule>

# #####
# # WEB PERFORMANCE #
# #####

# -----
# | Compression |
# -----

<IfModule mod_deflate.c>

    # Force compression for mangled headers.
    # http://developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-beyond-gzipping
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|def
(4,13)$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # Compress all output labeled with one of the following MIME-types
    # (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
    # and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
    # as `AddOutputFilterByType` is still in the core directives).
    <IfModule mod_filter.c>
        AddOutputFilterByType DEFLATE application/atom+xml \
                                application/javascript \
                                application/json \

```

```
application/rss+xml \
application/vnd.ms-fontobject \
application/x-font-ttf \
application/x-web-app-manifest+json \
application/xhtml+xml \
application/xml \
font/opentype \
image/svg+xml \
image/x-icon \
text/css \
text/html \
text/plain \
text/x-component \
text/xml
```

```
</IfModule>
```

```
</IfModule>
```

```
# -----
# | Content transformations |
# -----
```

```
# Prevent some of the mobile network providers from modifying the content of
# your site: http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.9.5.
```

```
# <IfModule mod_headers.c>
#   Header set Cache-Control "no-transform"
# </IfModule>
```

```
# -----
# | ETag removal |
# -----
```

```
# Since we're sending far-future expires headers (see below), ETags can
# be removed: http://developer.yahoo.com/performance/rules.html#etags.
```

```
# `FileETag None` is not enough for every server.
```

```
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>
```

FileETag None

```
# -----  
# | Expires headers (for better cache control) |  
# -----  
  
# The following expires headers are set pretty far in the future. If you don't  
# control versioning with filename-based cache busting, consider lowering the  
# cache time for resources like CSS and JS to something like 1 week.  
  
<IfModule mod_expires.c>  
  
    ExpiresActive on  
    ExpiresDefault "access plus 1 month"  
  
    # CSS  
    ExpiresByType text/css "access plus 1 year"  
  
    # Data interchange  
    ExpiresByType application/json "access plus 0 seconds"  
    ExpiresByType application/xml "access plus 0 seconds"  
    ExpiresByType text/xml "access plus 0 seconds"  
  
    # Favicon (cannot be renamed!)  
    ExpiresByType image/x-icon "access plus 1 week"  
  
    # HTML components (HTCs)  
    ExpiresByType text/x-component "access plus 1 month"  
  
    # HTML  
    ExpiresByType text/html "access plus 0 seconds"  
  
    # JavaScript  
    ExpiresByType application/javascript "access plus 1 year"  
  
    # Manifest files  
    ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"  
    ExpiresByType text/cache-manifest "access plus 0 seconds"  
  
    # Media  
    ExpiresByType audio/ogg "access plus 1 month"
```

```
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"
```

Web feeds

```
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"
```

Web fonts

```
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
```

```
</IfModule>
```