

```

# Set the default handler.
DirectoryIndex index.php index.html index.htm

# Prevent directory listing
Options -Indexes

# Make sure MultiViews is disabled if available.
<IfModule mod_negotiation.c>
    Options -MultiViews
</IfModule>

<FilesMatch "\.(dist|dtd|markdown|md|twig|yaml|yml)|(bower|composer|jsdoc|package)\.json$">
    <IfModule mod_authz_core.c>
        Require all denied
    </IfModule>
    <IfModule !mod_authz_core.c>
        Order deny,allow
        Deny from all
    </IfModule>
</FilesMatch>

<IfModule mod_rewrite.c>
    RewriteEngine on

    RewriteRule cache/ - [F]

    # Some servers require the RewriteBase to be set. If so, set to the correct folder.
    # RewriteBase /

    RewriteCond %{REQUEST_URI}::$1 ^(/.+)/(.*):;\2$
    RewriteRule ^(.*) - [E=BASE:%1]

    # Sets the HTTP_AUTHORIZATION header removed by Apache
    RewriteCond %{HTTP:Authorization} .
    RewriteRule ^ - [E=HTTP_AUTHORIZATION:%{HTTP:Authorization}]

    # Redirect to URI without front controller to prevent duplicate content
    # (with and without `/index.php`). Only do this redirect on the initial
    # rewrite by Apache and not on subsequent cycles. Otherwise we would get an
    # endless redirect loop (request -> rewrite to front controller ->
    # redirect -> request -> ...).

```



```
    RewriteRule "(1/)\." - [F]  
</IfModule>
```