

```

<FilesMatch "\.(ico|pdf|flv|jpg|jpeg|png|gif|js|css|swf)$">
Header set Cache-Control "max-age=172800, public"
</FilesMatch>

<IfModule mod_deflate.c>

# Force compression for mangled headers.
# http://developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-beyond-gzipping
<IfModule mod_setenvif.c>
<IfModule mod_headers.c>
SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\s*,?\s*)+([X"-]{4,13})$ HAVE_Accept-Encoding
RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
</IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
# as `AddOutputFilterByType` is still in the core directives).

<IfModule mod_filter.c>
AddOutputFilterByType DEFLATE application/atom+xml \
application/javascript \
application/x-javascript \
application/json \
application/rss+xml \
application/vnd.ms-fontobject \
application/x-font-ttf \
application/x-web-app-manifest+json \
application/xhtml+xml \
application/xml \
font/opentype \
image/svg+xml \
image/x-icon \
text/css \
text/html \
text/plain \
text/x-component \
text/xml
</IfModule>

```

```
</IfModule>
</IfModule>

<IfModule mod_expires.c>
# Enable expirations
ExpiresActive On
# Default directive
ExpiresDefault "access plus 1 month"
# My favicon
ExpiresByType image/x-icon "access plus 1 year"
# Images
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/jpg "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
# CSS
ExpiresByType text/css "access 1 month"
# Javascript
ExpiresByType application/javascript "access plus 1 year"
</IfModule>

# 1. To use URL Alias you need to be running apache with mod_rewrite enabled.

# 2. In your opencart directory rename htaccess.txt to .htaccess.

# For any support issues please visit: http://www.opencart.com

Options +FollowSymlinks

# Prevent Directory listing
Options -Indexes

# Prevent Direct Access to files
<FilesMatch "\.(tpl|ini|log)">
  Order deny,allow
  Deny from all
</FilesMatch>

# SEO URL Settings
RewriteEngine On
# If your opencart installation does not run on the main web folder make sure you folder
```

it does run in ie. / becomes /shop/

```
RewriteBase /  
RewriteRule ^sitemap.xml$ index.php?route=feed/google_sitemap [L]  
RewriteRule ^googlebase.xml$ index.php?route=feed/google_base [L]  
RewriteRule ^download/(.*) /index.php?route=error/not_found [L]  
RewriteCond %{REQUEST_FILENAME} !-f  
RewriteCond %{REQUEST_FILENAME} !-d  
RewriteCond %{REQUEST_URI} !.*\.(ico|gif|jpg|jpeg|png|js|css)  
RewriteRule ^([^\?]*)(.*) index.php?_route_=$1 [L,QSA]
```

*### Additional Settings that may need to be enabled for some servers
Uncomment the commands by removing the # sign in front of it.
If you get an "Internal Server Error 500" after enabling any of the following
settings, restore the # as this means your host doesn't allow that.*

*# 1. If your cart only allows you to add one item at a time, it is possible
register_globals is on. This may work to disable it:*

php_flag register_globals off

2. If your cart has magic quotes enabled, This may work to disable it:

php_flag magic_quotes_gpc Off

*# 3. Set max upload file size. Most hosts will limit this and not allow it to be
overridden but you can try*

php_value upload_max_filesize 999M

*# 4. set max post size. uncomment this line if you have a lot of product options or are
getting errors where forms are not saving all fields*

php_value post_max_size 999M

*# 5. set max time script can take. uncomment this line if you have a lot of product
options or are getting errors where forms are not saving all fields*

php_value max_execution_time 200

*# 6. set max time for input to be recieved. Uncomment this line if you have a lot of
product options or are getting errors where forms are not saving all fields*

php_value max_input_time 200

7. disable open_basedir limitations

php_admin_value open_basedir none

```
RewriteCond %{HTTP_HOST} ^babysitter\.co\.id$ [OR]
RewriteCond %{HTTP_HOST} ^www\.babysitter\.co\.id$
RewriteRule ^/?$ "http://www.pembantu.com/" [R=301,L]

RewriteCond %{HTTP_HOST} ^baju\.co$ [OR]
RewriteCond %{HTTP_HOST} ^www\.baju\.co$
RewriteRule ^/?$ "http://www.busana.com/baju" [R=301,L]

RewriteCond %{HTTP_HOST} ^barangelektronik\.co\.id$ [OR]
RewriteCond %{HTTP_HOST} ^www\.barangelektronik\.co\.id$
RewriteRule ^/?$ "http://www.barangelektronik.com" [R=301,L]

RewriteCond %{HTTP_HOST} ^busana\.cm$ [OR]
RewriteCond %{HTTP_HOST} ^www\.busana\.cm$
RewriteRule ^/?$ "http://www.busana.com" [R=301,L]

RewriteCond %{HTTP_HOST} ^busana\.co\.id$ [OR]
RewriteCond %{HTTP_HOST} ^www\.busana\.co\.id$
RewriteRule ^/?$ "http://www.busana.com" [R=301,L]

RewriteCond %{HTTP_HOST} ^busana\.co\.uk$ [OR]
RewriteCond %{HTTP_HOST} ^www\.busana\.co\.uk$
RewriteRule ^/?$ "http://www.busana.com" [R=301,L]

RewriteCond %{HTTP_HOST} ^busana\.net$ [OR]
RewriteCond %{HTTP_HOST} ^www\.busana\.net$
RewriteRule ^/?$ "http://www.busana.com" [R=301,L]

RewriteCond %{HTTP_HOST} ^busana\.org$ [OR]
RewriteCond %{HTTP_HOST} ^www\.busana\.org$
RewriteRule ^/?$ "http://www.busana.com" [R=301,L]

RewriteCond %{HTTP_HOST} ^sepatu\.co$ [OR]
RewriteCond %{HTTP_HOST} ^www\.sepatu\.co$
RewriteRule ^/?$ "http://www.busana.com/sepatu/" [R=301,L]

RewriteCond %{HTTP_HOST} ^kredit\.co\.id$ [OR]
RewriteCond %{HTTP_HOST} ^www\.kredit\.co\.id$
RewriteRule ^/?$ "http://kredit.com" [R=301,L]

RewriteCond %{HTTP_HOST} ^tokobagus\.cm$ [OR]
```

```
RewriteCond %{HTTP_HOST} ^www\.tokobagus\.cm$  
RewriteRule ^/?$ "http://www.busana.com" [R=301,L]  
  
RewriteCond %{HTTP_HOST} ^pembantu\.net$ [OR]  
RewriteCond %{HTTP_HOST} ^www\.pembantu\.net$  
RewriteRule ^/?$ "http://www.pembantu.com" [R=301,L]
```