

RedirectMatch 403 /\..*\$

<IfModule mod_rewrite.c>

RewriteEngine On

RewriteBase /

no www

RewriteCond %{HTTP_HOST} ^bendbabylove\. [NC]

RewriteRule ^(.)\$ http://www.bendbabylove.com/\$1 [R=301,L]*

REQUEST METHODS FILTERED

RewriteCond %{REQUEST_METHOD} ^(HEAD|TRACE|DELETE|TRACK|DEBUG) [NC]

RewriteRule ^(.*)\$ - [F,L]

Uploaded content

RewriteRule ^/?wp-content/uploads/(.*)\$ http://miacfiles.s3.amazonaws.com/wp-content/uploa

BPSQSE BPS QUERY STRING EXPLOITS

*# The libwww-perl User Agent is forbidden - Many bad bots use libwww-perl modules, but some
Good sites such as W3C use it for their W3C-LinkChecker.*

*# Add or remove user agents temporarily or permanently from the first User Agent filter by
If you want a list of bad bots / User Agents to block then scroll to the end of this file*

RewriteCond %{HTTP_USER_AGENT} (libwww-perl|wget|python|nikto|curl|scan|java|winhttp|clsh|

RewriteCond %{HTTP_USER_AGENT} (%0A|%0D|%27|%3C|%3E|%00) [NC,OR]

RewriteCond %{HTTP_USER_AGENT} (;|<|>|'|"|\)|\(|%0A|%0D|%22|%27|%28|%3C|%3E|%00).*(libwww-
perl|wget|python|nikto|curl|scan|java|winhttp|HTTrack|clsh|http|archiver|loader|email|harvest|

RewriteCond %{THE_REQUEST} \?\ HTTP/ [NC,OR]

RewriteCond %{THE_REQUEST} \/*\ HTTP/ [NC,OR]

RewriteCond %{THE_REQUEST} etc/passwd [NC,OR]

RewriteCond %{THE_REQUEST} cgi-bin [NC,OR]

RewriteCond %{THE_REQUEST} (%0A|%0D|\r|\n) [NC,OR]

RewriteCond %{REQUEST_URI} owssvr\.dll [NC,OR]

RewriteCond %{HTTP_REFERER} (%0A|%0D|%27|%3C|%3E|%00) [NC,OR]

RewriteCond %{HTTP_REFERER} \.opendirviewer\. [NC,OR]

RewriteCond %{HTTP_REFERER} users\.skynet\.be.* [NC,OR]

RewriteCond %{QUERY_STRING} [a-zA-Z0-9_]=http:// [OR]

RewriteCond %{QUERY_STRING} [a-zA-Z0-9_]=(\.\.//?)+ [OR]

RewriteCond %{QUERY_STRING} [a-zA-Z0-9_]=/[a-z0-9_]//?+ [NC,OR]

RewriteCond %{QUERY_STRING} \=PHP[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}

RewriteCond %{QUERY_STRING} (\.\.//|\.\.) [OR]

RewriteCond %{QUERY_STRING} ' [NC,OR]

```

RewriteCond %{QUERY_STRING} http: [NC,OR]
RewriteCond %{QUERY_STRING} https: [NC,OR]
RewriteCond %{QUERY_STRING} \=|\u\ [NC,OR]
RewriteCond %{QUERY_STRING} ^(\.+)/self/(\.)*$ [NC,OR]
RewriteCond %{QUERY_STRING} ^(\.+)cPath=http://(\.)*$ [NC,OR]
RewriteCond %{QUERY_STRING} (<|\%3C).*script.*(>|\%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<|\%3C)([^\s]*s)+cript.*(>|\%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<|\%3C).*embed.*(>|\%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<|\%3C)([^\e]*e)+mbed.*(>|\%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<|\%3C).*object.*(>|\%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<|\%3C)([^\o]*o)+bject.*(>|\%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<|\%3C).*iframe.*(>|\%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<|\%3C)([^\i]*i)+frame.*(>|\%3E) [NC,OR]
RewriteCond %{QUERY_STRING} base64_encode.*\(\.)* [NC,OR]
RewriteCond %{QUERY_STRING} base64_(en|de)code[^\(\[^\)]*\) [NC,OR]
RewriteCond %{QUERY_STRING} GLOBALS(=| \[| \%00-\%20) [OR]
RewriteCond %{QUERY_STRING} _REQUEST(=| \[| \%00-\%20) [OR]
RewriteCond %{QUERY_STRING} ^.*\(|\)|\!|\<|\>|\%3c|\%3e|\%5b|\%5d).* [NC,OR]
RewriteCond %{QUERY_STRING} ^.*\(\x00|\x04|\x08|\x0d|\x1b|\x20|\x3c|\x3e|\x5b|\x5d|\x7f).*
RewriteCond %{QUERY_STRING} (NULL|OUTFILE|LOAD_FILE) [OR]
RewriteCond %{QUERY_STRING} (\.\/|\.\.\/|\.\.\.\/)+(motd|etc|bin) [NC,OR]
RewriteCond %{QUERY_STRING} (localhost|loopback|127\.\.0\.\.1) [NC,OR]
RewriteCond %{QUERY_STRING} (<|\>|'| %0A| %0D| %27| %3C| %3E| %00) [NC,OR]
RewriteCond %{QUERY_STRING} concat[^\(\)]*\([ [NC,OR]
RewriteCond %{QUERY_STRING} union([^\s]*s)+elect [NC,OR]
RewriteCond %{QUERY_STRING} union([^\a]*a)+11([^\s]*s)+elect [NC,OR]
RewriteCond %{QUERY_STRING} (;|<|\>|'| | \)| %0A| %0D| %22| %27| %3C| %3E| %00).*
(<\/\*| union| select| insert| drop| delete| update| cast| create| char| convert| alter| declare| order| scr
[NC,OR]
RewriteCond %{QUERY_STRING} (sp_executesql) [NC]
RewriteRule ^(\.)*$ - [F,L]

RewriteRule ^index\.php$ - [L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /index.php [L]
</IfModule>

```