

```
#Special provider line to disable register_globals
SetEnv PHP_VER 5_4
SetEnv REGISTER_GLOBALS 0

#
# Apache/PHP/Drupal settings:
#

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engine|incl|info|install|make|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?|xhtml|svn-
base)$|^(\code-style|.p|Entries.*|Repository|Root|Tag|Template|all-
wcprops|entries|format)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Set the default handler.
DirectoryIndex index.php

# Override PHP settings. More in sites/default/settings.php
# but the following cannot be changed at runtime.

# PHP 4, Apache 1.
<IfModule mod_php4.c>
    php_value magic_quotes_gpc 0
    php_value magic_quotes_runtime 0
```

```
php_value register_globals 0
php_value session.auto_start 0
php_value mbstring.http_input pass
php_value mbstring.http_output pass
php_value mbstring.encoding_translation 0
</IfModule>
```

PHP 4, Apache 2.

```
<IfModule sapi_apache2.c>
php_value magic_quotes_gpc 0
php_value register_globals 0
php_value session.auto_start 0
php_value mbstring.http_input pass
php_value mbstring.http_output pass
php_value mbstring.encoding_translation 0
</IfModule>
```

PHP 5, Apache 1 and 2.

```
<IfModule mod_php5.c>
php_value magic_quotes_gpc 0
php_value register_globals 0
php_value session.auto_start 0
php_value mbstring.http_input pass
php_value mbstring.http_output pass
php_value mbstring.encoding_translation 0
</IfModule>
```

Requires mod_expires to be enabled.

```
<IfModule mod_expires.c>
```

```
# Enable expirations.
```

```
ExpiresActive On
```

```
# Cache all files for 2 weeks after access (A).
```

```
ExpiresDefault A1209600
```

```
<FilesMatch \.php$>
```

```
# Do not allow PHP scripts to be cached unless they explicitly send cache
# headers themselves. Otherwise all scripts would have to overwrite the
# headers set by mod_expires if they want another caching behavior. This may
# fail if an error occurs early in the bootstrap process, and it may cause
# problems if a non-Drupal PHP file is installed in a subdirectory.
```

```
ExpiresDefault A0
```

```
ExpiresActive Off
</FilesMatch>
</IfModule>

# Various rewrite rules.
<IfModule mod_rewrite.c>
    RewriteEngine on

    # If your site can be accessed both with and without the 'www.' prefix, you
    # can use one of the following settings to redirect users to your preferred
    # URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
    #
    # To redirect all users to access the site WITH the 'www.' prefix,
    # (http://example.com/... will be redirected to http://www.example.com/...)
    # adapt and uncomment the following:
    # RewriteCond %{HTTP_HOST} ^example\.com$ [NC]
    # RewriteRule ^(.*)$ http://www.example.com/$1 [L,R=301]
    #
    # To redirect all users to access the site WITHOUT the 'www.' prefix,
    # (http://www.example.com/... will be redirected to http://example.com/...)
    # uncomment and adapt the following:
    # RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]
    # RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]

    # Modify the RewriteBase if you are using Drupal in a subdirectory or in a
    # VirtualDocumentRoot and the rewrite rules are not working properly.
    # For example if your site is at http://example.com/drupal uncomment and
    # modify the following line:
    # RewriteBase /drupal
    #
    # If your site is running in a VirtualDocumentRoot at http://example.com/,
    # uncomment the following line:
    # RewriteBase /

    ### BOOST START ###

    # Gzip Cookie Test
    RewriteRule ^(.*)boost-gzip-cookie-test\.html cache/perm/boost-gzip-cookie-
test\.html\.gz [L,T=text/html,E=no-gzip:1]

    # Caching for anonymous users
```

```
# Skip boost IF not get request OR uri has wrong dir OR cookie is set OR request came from this server OR https request
```

```
RewriteCond %{REQUEST_METHOD} !^(GET|HEAD)$ [OR]
```

```
RewriteCond %{REQUEST_URI}
```

```
(</admin|cache/misc/modules/sites/system/openid/themes/node/add/comment/reply>|
```

```
</edit|user/user/<login|password/register>)&#92; [OR]
```

```
RewriteCond %{HTTP:Pragma} no-cache [OR]
```

```
RewriteCond %{HTTP:Cache-Control} no-cache [OR]
```

```
RewriteCond %{HTTPS} on [OR]
```

```
RewriteCond %{HTTP_COOKIE} DRUPAL_UID
```

```
RewriteRule .* - [S=3]
```

```
# GZIP
```

```
RewriteCond %{HTTP_COOKIE} !(boost-gzip)
```

```
RewriteCond %{HTTP:Accept-encoding} !gzip
```

```
RewriteRule .* - [S=1]
```

```
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%
```

```
{QUERY_STRING}\.html\..gz -s
```

```
RewriteRule .* cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{QUERY_STRING}\.html\..gz
```

```
[L,T=text/html,E=no-gzip:1]
```

```
# NORMAL
```

```
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%
```

```
{QUERY_STRING}\.html -s
```

```
RewriteRule .* cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{QUERY_STRING}\.html
```

```
[L,T=text/html]
```

```
### BOOST END ###
```

```
# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_URI} !=/favicon.ico
```

```
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
```

```
</IfModule>
```

```
# $Id$
```