

Options +ExecCGI

Allow execution of .cgi scripts.

```
AddHandler cgi-script .cgi
```

Protect files and directories from prying eyes.

```
<FilesMatch "\.
```

```
(lua|engine|incl|info|install|module|profile|test|pol|sh|. *sql|theme|tpl(\.html)?|x|tmp|svn-  
base)$|^(\. *|code-style\.|pl|Entries.*|Repository|Root|Tag|Template|all-  
w|props|entries|format)$">
```

```
    Order allow,deny
```

```
</FilesMatch>
```

Handle any 404 errors.

```
ErrorDocument 404 /index.cgi
```

Set the default handler.

```
DirectoryIndex index.cgi
```

Force simple error message for requests for non-existent favicon.ico.

```
<Files favicon.ico>
```

There is no end quote below, for compatibility with Apache 1.3.

```
ErrorDocument 404 "The requested file favicon.ico was not found.
```

```
</Files>
```

Etags rules.

```
<IfModule mod_headers.c>
```

```
    # Disabled:
```

```
    # FileETag None
```

```
    # Enable Etags:
```

```
    # FileETag MTime Size
```

```
    # Enable Etags in a clustered environment:
```

```
    # FileETag MTime Size
```

```
</IfModule>
```

Various rewrite rules.

```
<IfModule mod_rewrite.c>
```

```
    RewriteEngine on
```

```
# Do not allow access to "hidden" directories whose names begin with period.
# NOTE: This only works when mod_rewrite is loaded.
RewriteRule "(^/)\." - [F]

# Rewrite URLs of the form 'x' to the form 'index.cgi?q=x'.
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} !=/favicon.ico
# Don't care about image files
RewriteCond %{REQUEST_URI} !\.(jpg|JPG|gif|GIF|png|PNG|ico|ICO|svg|SVG)$
RewriteRule ^(.*)$ index.cgi [L]
</IfModule>
```