

```
### SILVERSTRIPE START ###
```

```
# Deny access to templates (but allow from localhost)
```

```
<Files *.ss>  
  Order deny,allow  
  Deny from all  
  Allow from 127.0.0.1  
</Files>
```

```
# Deny access to IIS configuration
```

```
<Files web.config>  
  Order deny,allow  
  Deny from all  
</Files>
```

```
# Deny access to YAML configuration files which might include sensitive information
```

```
<Files ~ "\.ya?ml$">  
  Order allow,deny  
  Deny from all  
</Files>
```

```
# Route errors to static pages automatically generated by SilverStripe
```

```
ErrorDocument 404 /assets/error-404.html  
ErrorDocument 500 /assets/error-500.html
```

```
<IfModule mod_rewrite.c>
```

```
  SetEnv HTTP_MOD_REWRITE On  
  RewriteEngine On
```

```
# Deny access to potentially sensitive files and folders
```

```
RewriteRule ^vendor(/|$) - [F,L,NC]  
RewriteRule silverstripe-cache(/|$) - [F,L,NC]  
RewriteRule composer\.(json|lock) - [F,L,NC]
```

```
# Process through SilverStripe if no file with the requested name exists.
```

```
# Pass through the original path as a query parameter, and retain the existing  
parameters.
```

```
RewriteCond %{REQUEST_URI} ^(.*)*$  
RewriteCond %{REQUEST_FILENAME} !-f  
RewriteRule .* framework/main.php?url=%1 [QSA]
```

If framework isn't in a subdirectory, rewrite to installer

RewriteCond %{REQUEST_URI} ^(.*)/framework/main.php\$

RewriteCond %{REQUEST_FILENAME} !-f

RewriteRule . %1/install.php? [R,L]

</IfModule>

SILVERSTRIPE END