

```
# Prevent Apache from returning a 404 error for a rewrite if a directory
# with the same name does not exist.
# http://httpd.apache.org/docs/current/content-negotiation.html#multiviews
Options -MultiViews

# Use UTF-8 encoding for anything served as `text/html` or `text/plain`.
AddDefaultCharset utf-8

# Force UTF-8 for certain file formats.
<IfModule mod_mime.c>
    AddCharset utf-8 .atom .css .js .json .rss .vtt .webapp .xml
</IfModule>

# Activates URL rewriting (like myproject.com/controller/action/1/2/3)
RewriteEngine On

# Disallows others to look into folder
# Options -Indexes

RewriteBase /

# Redirect Trailing Slashes...
RewriteRule ^(.*)/$ $1 [L,R=301]

# Redirect www.domain.de to domain.de
<IfModule mod_rewrite.c>
    RewriteCond %{HTTPS} !=on
    RewriteCond %{HTTP_HOST} ^www\.(.+) [NC]
    RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
</IfModule>

# General rewrite rules
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-l

RewriteRule ^(.+)$ index.php?url=$1 [QSA,L]

# #####
# # WEB PERFORMANCE #
# #####
```

```

# #####

# -----
# | Compression |
# -----

<IfModule mod_deflate.c>

    # Force compression for mangled headers.
    # http://developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-beyond-gzipping
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)l ~(15)l -(15))$
^((gzip|deflate)\s*,?\s*)+ [X"-]{4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # Compress all output labeled with one of the following MIME-types
    # (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
    # and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
    # as `AddOutputFilterByType` is still in the core directives).
    <IfModule mod_filter.c>
        AddOutputFilterByType DEFLATE application/atom+xml \
            application/javascript \
            application/json \
            application/rss+xml \
            application/vnd.ms-fontobject \
            application/x-font-ttf \
            application/x-web-app-manifest+json \
            application/xhtml+xml \
            application/xml \
            font/opentype \
            image/svg+xml \
            image/x-icon \
            text/css \
            text/html \
            text/plain \
            text/x-component \
            text/xml
    </IfModule>

```

```
</IfModule>
```

```
# -----  
# | ETag removal |  
# -----
```

```
# Since we're sending far-future expires headers (see below), ETags can  
# be removed: http://developer.yahoo.com/performance/rules.html#etags.
```

```
# `FileETag None` is not enough for every server.
```

```
<IfModule mod_headers.c>
```

```
Header unset ETag
```

```
</IfModule>
```

```
FileETag None
```

```
# -----  
# | Expires headers (for better cache control) |  
# -----
```

```
# The following expires headers are set pretty far in the future. If you don't  
# control versioning with filename-based cache busting, consider lowering the  
# cache time for resources like CSS and JS to something like 1 week.
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
```

```
ExpiresDefault "access plus 1 month"
```

```
# CSS
```

```
ExpiresByType text/css "access plus 1 year"
```

```
# Data interchange
```

```
ExpiresByType application/json "access plus 0 seconds"
```

```
ExpiresByType application/xml "access plus 0 seconds"
```

```
ExpiresByType text/xml "access plus 0 seconds"
```

```
# Favicon (cannot be renamed!)
```

```
ExpiresByType image/x-icon "access plus 1 week"
```

```

# HTML components (HTCs)
ExpiresByType text/x-component "access plus 1 month"

# HTML
ExpiresByType text/html "access plus 0 seconds"

# JavaScript
ExpiresByType application/javascript "access plus 1 year"

# Manifest files
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"

# Media
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# Web feeds
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"

# Web fonts
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"

```

```
</IfModule>
```