

```

#
# Apache/PHP/Drupal settings:
#

# Protect files and directories from prying eyes.
<FilesMatch "\.(engine|incl|info|install|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?|
|tmp|svn-base)$|^(\code-style|.pl|Entries.*|Repository|Root|Tag|Template|all-
wcp|props|entries|format)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
# For security reasons, Option followsymlinks cannot be overridden.
#Options +FollowSymLinks
Options +SymLinksIfOwnerMatch

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Set the default handler.
DirectoryIndex index.php

# Override PHP settings. More in sites/default/settings.php
# but the following cannot be changed at runtime.

# PHP 4, Apache 1.
<IfModule mod_php4.c>
    php_value magic_quotes_gpc          0
    php_value register_globals          0
    php_value session.auto_start       0
    php_value mbstring.http_input      pass
    #php_value mbstring.encoding_transl
    -----

```

```
php_value mbstring.http_output      pass
php_value mbstring.encoding_translation 0
</IfModule>
```

*# PHP 4, Apache 2.*

```
<IfModule sapi_apache2.c>
php_value magic_quotes_gpc          0
php_value register_globals           0
php_value session.auto_start        0
php_value mbstring.http_input        pass
php_value mbstring.http_output       pass
php_value mbstring.encoding_translation 0
</IfModule>
```

*# PHP 5, Apache 1 and 2.*

```
<IfModule mod_php5.c>
php_value magic_quotes_gpc          0
php_value register_globals           0
php_value session.auto_start        0
php_value mbstring.http_input        pass
php_value mbstring.http_output       pass
php_value mbstring.encoding_translation 0
</IfModule>
```

*# Requires mod\_expires to be enabled.*

```
<IfModule mod_expires.c>
  # Enable expirations.
  ExpiresActive On

  # Cache all files for 2 weeks after access (A).
  ExpiresDefault A1209600
```

```
<FilesMatch \.php$>
```

```
  # Do not allow PHP scripts to be cached unless they explicitly send cache
  # headers themselves. Otherwise all scripts would have to overwrite the
  # headers set by mod_expires if they want another caching behavior. This may
  # fail if an error occurs early in the bootstrap process, and it may cause
  # problems if a non-Drupal PHP file is installed in a subdirectory.
```

```
  ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```

```

# Various rewrite rules.
<IfModule mod_rewrite.c>
  RewriteEngine on

  # If your site can be accessed both with and without the 'www.' prefix, you
  # can use one of the following settings to redirect users to your preferred
  # URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
  #
  # To redirect all users to access the site WITH the 'www.' prefix,
  # (http://example.com/... will be redirected to http://www.example.com/...)
  # adapt and uncomment the following:

  #RewriteCond %{HTTP_HOST} ^widgetcity\.com\.ph$ [NC]
  #RewriteRule ^(.*)$ http://www.widgetcity.com.ph/$1 [L,R=301]

  RewriteCond %{REQUEST_URI} !(^/(.*)\.js|.css|.jpg|.jpeg|.png|.gif)) [NC]
  RewriteCond %{HTTP_HOST} ^i.widgetcity\.com\.ph$ [NC]
  RewriteRule ^(.*)$ http://www.widgetcity.com.ph/$1 [L,R=301]

  #
  # To redirect all users to access the site WITHOUT the 'www.' prefix,
  # (http://www.example.com/... will be redirected to http://example.com/...)
  # uncomment and adapt the following:
  # RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]
  # RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]

  # Modify the RewriteBase if you are using Drupal in a subdirectory or in a
  # VirtualDocumentRoot and the rewrite rules are not working properly.
  # For example if your site is at http://example.com/drupal uncomment and
  # modify the following line:
  # RewriteBase /drupal
  #
  # If your site is running in a VirtualDocumentRoot at http://example.com/,
  # uncomment the following line:
  # RewriteBase /

  ### BOOST START ###

  # Gzip Cookie Test
  RewriteRule ^(.*)boost-gzip-cookie-test\.html cache/perm/boost-gzip-cookie-

```

```
test\.html\.gz [L, T=text/html, E=no-gzip: 1]
```

```
# GZIP - Cached css & js files
```

```
RewriteCond %{HTTP_COOKIE} !(boost-gzip)
```

```
RewriteCond %{HTTP: Accept-encoding} !gzip
```

```
RewriteRule .* - [S=2]
```

```
RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{HTTP_HOST}%{REQUEST_URI}_.css\.gz -s
```

```
RewriteRule .* cache/perm/%{HTTP_HOST}%{REQUEST_URI}_.css\.gz [L, QSA, T=text/css, E=no-gzip: 1]
```

```
RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{HTTP_HOST}%{REQUEST_URI}_.js\.gz -s
```

```
RewriteRule .* cache/perm/%{HTTP_HOST}%{REQUEST_URI}_.js\.gz
```

```
[L, QSA, T=text/javascript, E=no-gzip: 1]
```

```
# NORMAL - Cached css & js files
```

```
RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{HTTP_HOST}%{REQUEST_URI}_.css -s
```

```
RewriteRule .* cache/perm/%{HTTP_HOST}%{REQUEST_URI}_.css [L, QSA, T=text/css]
```

```
RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{HTTP_HOST}%{REQUEST_URI}_.js -s
```

```
RewriteRule .* cache/perm/%{HTTP_HOST}%{REQUEST_URI}_.js [L, QSA, T=text/javascript]
```

```
# Caching for anonymous users
```

```
# Skip boost IF not get request OR uri has wrong dir OR cookie is set OR request came from this server OR https request
```

```
RewriteCond %{REQUEST_METHOD} !^(GET|HEAD)$ [OR]
```

```
RewriteCond %{REQUEST_URI}
```

```
(</admin|cache/misc/modules/sites/system/openid/themes/node/add/comment/reply)|
```

```
(</edit|user/user/<login|password/register))$) [OR]
```

```
RewriteCond %{HTTPS} on [OR]
```

```
RewriteCond %{HTTP_COOKIE} DRUPAL_UID
```

```
RewriteRule .* - [S=5]
```

```
# GZIP
```

```
RewriteCond %{HTTP_COOKIE} !(boost-gzip)
```

```
RewriteCond %{HTTP: Accept-encoding} !gzip
```

```
RewriteRule .* - [S=2]
```

```
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{HTTP_HOST}%{REQUEST_URI}_%
```

```
{QUERY_STRING}\.html\.gz -s
```

```
RewriteRule .* cache/normal/%{HTTP_HOST}%{REQUEST_URI}_%{QUERY_STRING}\.html\.gz
```

```
[L, T=text/html, E=no-gzip: 1]
```

```
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{HTTP_HOST}%{REQUEST_URI}_%
```

```
{QUERY_STRING}\.xml\.gz -s
```

```
RewriteRule .* cache/normal/%{HTTP_HOST}%{REQUEST_URI}_%{QUERY_STRING}\.xml\.gz
```

```
[L, T=text/xml, E=no-gzip: 1]
```

```
# NORMAL
```

```
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{HTTP_HOST}%{REQUEST_URI}_%  
{QUERY_STRING}\.html -s
```

```
RewriteRule .* cache/normal/%{HTTP_HOST}%{REQUEST_URI}_%{QUERY_STRING}\.html  
[L, T=text/html]
```

```
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{HTTP_HOST}%{REQUEST_URI}_%  
{QUERY_STRING}\.xml -s
```

```
RewriteRule .* cache/normal/%{HTTP_HOST}%{REQUEST_URI}_%{QUERY_STRING}\.xml  
[L, T=text/xml]
```

```
### BOOST END ###
```

```
# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_URI} !=/favicon.ico
```

```
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
```

```
</IfModule>
```

```
# $Id: .htaccess,v 1.90.2.4 2009/12/07 12:00:40 goba Exp $
```

```
<IfModule mod_deflate.c>
```

```
<FilesMatch "\.(js|css|html|html|php|xml|txt)$">
```

```
SetOutputFilter DEFLATE
```

```
# Exclude Not compatible browsers (uncomment to activate)
```

```
BrowserMatch ^Mozilla/4 gzip-only-text/html
```

```
BrowserMatch ^Mozilla/4\.0[678] no-gzip
```

```
BrowserMatch \bMSIE[ ] !no-gzip !gzip-only-text/html
```

```
</FilesMatch>
```

```
<IfModule mod_headers.c>
```

```
# properly handle requests coming from behind proxies
```

```
Header append Vary User-Agent
```

```
</IfModule>
```

```
</IfModule>
```

```
<filesmatch "\.(ico|flv|jpg|jpeg|png|gif|swf)$">
```

```
RequestHeader unset Cookie
```

```
Header unset Set-Cookie
```

```
Header set Cache-Control "max-age=2678400, public"
```

```
</filesmatch>
```

```
# Cache HTML files for a 1 hour
<filesmatch "\.(html|htm)$">
  Header set Cache-Control "max-age=3600, private, must-revalidate"
</filesmatch>
# Cache PDFs for a day
<filesmatch "\.(pdf)$">
  Header set Cache-Control "max-age=86400, public"
</filesmatch>
# Cache CSS for 31 days
<filesmatch "\.(css|css.gz)$">
  RequestHeader unset Cookie
  Header unset Set-Cookie
  Header set Cache-Control "max-age=2678400, private"
</filesmatch>
# Cache Javascripts for 31 days
<filesmatch "\.(js|js.gz)$">
  Header set Cache-Control "max-age=2678400, private"
  RequestHeader unset Cookie
  Header unset Set-Cookie
</filesmatch>

Header append Vary Accept-Encoding
# Turn ETags Off
<IfModule mod_headers.c>
Header unset ETag
</IfModule>

FileETag None
```