

```
#####
## uncomment these lines for CGI mode
## make sure to specify the correct cgi php binary file name
## it might be /cgi-bin/php-cgi

#   Action php5-cgi /cgi-bin/php5-cgi
#   AddHandler php5-cgi .php

#####
## GoDaddy specific options

#   Options -MultiViews

## you might also need to add this line to php.ini
##   cgi.fix_pathinfo = 1
## if it still doesn't work, rename php.ini to php5.ini

#####
## this line is specific for 1and1 hosting

    #AddType x-mapp-php5 .php
    #AddHandler x-mapp-php5 .php

#####
## default index file

    DirectoryIndex index.php

<IfModule mod_php5.c>

#####
## adjust memory limit

#   php_value memory_limit 64M
    php_value memory_limit 256M
    php_value max_execution_time 18000

#####
## disable magic quotes for php request vars

    -the flag magic_quotes_gpc off
```

```
php_flag magic_quotes_gpc off
```

```
#####
```

```
## disable automatic session start  
## before autoload was initialized
```

```
php_flag session.auto_start off
```

```
#####
```

```
## enable resulting html compression
```

```
php_flag zlib.output_compression on
```

```
#####
```

```
## disable user agent verification to not break multiple image upload
```

```
php_flag suhosin.session.cryptua off
```

```
#####
```

```
## turn off compatibility with PHP4 when dealing with objects
```

```
php_flag zend.zel_compatibility_mode Off
```

```
</IfModule>
```

```
<IfModule mod_security.c>
```

```
#####
```

```
## disable POST processing to not break multiple image upload
```

```
SecFilterEngine Off
```

```
SecFilterScanPOST Off
```

```
</IfModule>
```

```
<IfModule mod_deflate.c>
```

```
SetOutputFilter DEFLATE
```

```
<IfModule mod_setenvif.c>
```

```
## Netscape 4.x has some problems...
```

```
BrowserMatch ^Mozilla/4 gzip-only-text/html
```

```
## Netscape 4.06-4.08 have some more problems
```

```
BrowserMatch ^Mozilla/4.0 [6-8] .* gzip-only-text/html
```

```
BrowserMatch ^Mozilla/4\.0[678] no-gzip
```

```
# MSIE masquerades as Netscape, but it is fine  
# BrowserMatch \bMSIE !no-gzip !gzip-only-text/html
```

```
# NOTE: Due to a bug in mod_setenvif up to Apache 2.0.48  
# the above regex won't work. You can use the following  
# workaround to get the desired effect:
```

```
BrowserMatch \bMSIE[E] !no-gzip !gzip-only-text/html
```

```
# Don't compress images
```

```
SetEnvIfNoCase Request_URI \.(?:gif|jpe?g|png)$ no-gzip dont-vary
```

```
</IfModule>
```

```
<IfModule mod_headers.c>
```

```
# Make sure proxies don't deliver the wrong content
```

```
Header set Connection keep-alive
```

```
#Header append Vary User-Agent env=!dont-vary
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_ssl.c>
```

```
#####  
## make HTTPS env vars available for CGI mode
```

```
SSLOptions StdEnvVars
```

```
</IfModule>
```

```
<IfModule mod_rewrite.c>
```

```
#####  
## enable rewrites
```

```
Options +FollowSymLinks
```

```
RewriteEngine on
```

```
#####  
## you can put here your magento root folder
```

```
## path relative to web root

#RewriteBase /magento/

#####
## uncomment next line to enable light API calls processing

# RewriteRule ^api/([a-z][0-9a-z]+)/?$ api.php?type=$1 [QSA,L]

#####
## rewrite API2 calls to api.php (by now it is REST only)

RewriteRule ^api/rest api.php?type=rest [QSA,L]

#####
## workaround for HTTP authorization
## in CGI environment

RewriteRule .* - [E=HTTP_AUTHORIZATION:%{HTTP:Authorization}]

#####
## TRACE and TRACK HTTP methods disabled to prevent XSS attacks

RewriteCond %{REQUEST_METHOD} ^TRAC[EK]
RewriteRule .* - [L,R=405]

#####
## redirect for mobile user agents

#RewriteCond %{REQUEST_URI} !^/mobiledirectoryhere/.*$
#RewriteCond %{HTTP_USER_AGENT} "android|blackberry|ipad|iphone|ipod|iemobile|opera
mobile|palms|webos|googlebot-mobile" [NC]
#RewriteRule ^(.*)$ /mobiledirectoryhere/ [L,R=302]

#####

## always send 404 on missing files in these folders

RewriteCond %{REQUEST_URI} !^(media|skin|js)/

#####
```

```
## never rewrite for existing files, directories and links

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-l

#####
## rewrite everything else to index.php

RewriteRule .* index.php [L]

</IfModule>

#####
## Prevent character encoding issues from server overrides
## If you still have problems, use the second line instead

AddDefaultCharset Off
#AddDefaultCharset UTF-8

<IfModule mod_expires.c>

#####
## Add default Expires header
## http://developer.yahoo.com/performance/rules.html#expires

ExpiresActive On
ExpiresDefault "access plus 1 year"

</IfModule>

#####
## By default allow all access

Order allow,deny
Allow from all

#####
## Deny access to release notes to prevent disclosure of the installed Magento version

<Files RELEASE_NOTES.txt>
```

```
order allow,deny
deny from all
</Files>
```

```
#####
```

```
## If running in cluster environment, uncomment this
```

```
## http://developer.yahoo.com/performance/rules.html#etags
```