

DirectoryIndex index.html

FileETag MTime Size

<IfModule mod_expires.c>

ExpiresActive on

ExpiresDefault "access plus 0 seconds"

</IfModule>

<IfModule mod_mime.c>

Audio

AddType audio/mp4 m4a f4a f4b

AddType audio/ogg oga ogg

JavaScript

Normalize to standard type (it's sniffed in IE anyways):

<http://tools.ietf.org/html/rfc4329#section-7.2>

AddType application/javascript js

AddType application/json json

Video

AddType video/mp4 f4v f4p m4v mp4

AddType video/ogg ogv

AddType video/webm webm

AddType video/x-flv flv

Web fonts

AddType application/font-woff woff

AddType application/vnd.ms-fontobject eot

Browsers usually ignore the font MIME types and sniff the content,

however, Chrome shows a warning if other MIME types are used for the

following fonts.

AddType application/x-font-ttf ttc ttf

AddType font/opentype otf

Make SVGZ fonts work on iPad:

<https://twitter.com/FontSquirrel/status/14855840545>

AddType image/svg+xml svgz

AddType image/svg+xml --

```
HeaderEncoding gzip
```

```
svgz
```

```
# Other
```

```
AddType application/octet-stream
```

```
safariextz
```

```
AddType application/x-chrome-extension
```

```
crx
```

```
AddType application/x-opera-extension
```

```
oex
```

```
AddType application/x-web-app-manifest+json
```

```
webapp
```

```
AddType application/x-xpinstall
```

```
xpi
```

```
AddType application/xml
```

```
atom rdf rss xml
```

```
AddType image/webp
```

```
webp
```

```
AddType image/x-icon
```

```
cur
```

```
AddType text/vtt
```

```
vtt
```

```
AddType text/x-component
```

```
htc
```

```
AddType text/x-vcard
```

```
vcf
```

```
# Required for AppCache to work...
```

```
AddType text/cache-manifest
```

```
appcache
```

```
</IfModule>
```

```
<IfModule mod_headers.c>
```

```
Header set Content-Security-Policy "default-src 'self' https://lorempixel.com  
https://www.google-analytics.com"
```

```
Header set X-Content-Security-Policy "default-src 'self' https://lorempixel.com  
https://www.google-analytics.com"
```

```
Header set X-WebKit-CSP "default-src 'self' https://lorempixel.com https://www.google-  
analytics.com"
```

```
<FilesMatch "\.(appcache|crx|css|curl|eot|gif|htc|ico|jpe?  
|js|m4a|m4v|manifest|mp4|oex|ogal|ogg|ogv|otf|pdf|png|safariextz|svgz?  
|ttf|vcf|webapp|webml|webp|woff|xml|xpi)$">
```

```
Header unset Content-Security-Policy
```

```
Header unset X-Content-Security-Policy
```

```
Header unset X-WebKit-CSP
```

```
</FilesMatch>
```

```
<FilesMatch "\.(ico|pdf|flv|jpg|jpeg|png|gif|js|css|ngl|swf)$">
```

```
Header set Cache-Control "public"
```

```
</FilesMatch>
```

```
</IfModule>
```

```
# gzip compression.
```

```
<IfModule mod_deflate.c>
```

```
# html, xml, css, and js:
```

```
add_header Cache-Control public
```

```
AddOutputFilterByType DEFLATE text/html text/plain text/xml text/css application/x-  
javascript text/javascript application/javascript application/json  
# webfonts and svg;  
<FilesMatch "\.(ttf|otf|eot|svg)$" >  
    SetOutputFilter DEFLATE  
</FilesMatch>  
</IfModule>  
  
# -----  
# | File access |  
# -----  
  
# Block access to directories without a default document.  
# Usually you should leave this uncommented because you shouldn't allow anyone  
# to surf through every directory on your server (which may includes rather  
# private places like the CMS' s directories).  
  
<IfModule mod_autoindex.c>  
    Options -Indexes  
</IfModule>
```