

```

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Make HTMLy handle any 404 errors.
ErrorDocument 404 /index.php

# Set the default handler.
DirectoryIndex index.php index.html index.htm

# Requires mod_expires to be enabled.
<IfModule mod_expires.c>

    # to activate mode_expires
    ExpiresActive on

    ExpiresDefault "access plus 1 month"

    # For CSS
    ExpiresByType text/css "access plus 1 month"

    # For Data interchange
    ExpiresByType application/json "access plus 0 seconds"
    ExpiresByType application/xml "access plus 0 seconds"
    ExpiresByType text/xml "access plus 0 seconds"

    # For Favicon
    ExpiresByType image/x-icon "access plus 1 year"

    # For HTML components (HTCs)
    ExpiresByType text/x-component "access plus 1 month"

    # For HTML
    ExpiresByType text/html "access plus 1 month"

    # For JavaScript
    ExpiresByType application/javascript "access plus 1 month"

    # For Manifest files
    ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
    ExpiresByType text/cache-manifest "access plus 0 seconds"

```

For Media

```
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"
```

For Web feeds

```
ExpiresByType application/atom+xml "access plus 1 day"
ExpiresByType application/rss+xml "access plus 1 day"
```

For Web fonts

```
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
```

</IfModule>

Various rewrite rules.

<IfModule mod_rewrite.c>

RewriteEngine on

Uncomment the following to redirect all visitors to the www version

RewriteCond %{HTTP_HOST} !^www\. [NC]

RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [L,R=301]

Uncomment the following to redirect all visitors to non www version

RewriteCond %{HTTP_HOST} ^www\. (.+)\$ [NC]

RewriteRule ^ http://%1%{REQUEST_URI} [L,R=301]

If your site is running in a VirtualDocumentRoot at http://example.com/,

uncomment the following line:

RewriteBase /

Pass all requests not referring directly to files in the filesystem to index.php.

```

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^ index.php [L]

</IfModule>

# Enable Gzip compression.
<IfModule mod_deflate.c>

    # Force compression for mangled headers.
    # http://developer.yahoo.com/blogs/ym/2010/12/pushing-beyond-gzipping
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
            ^((gzip|deflate)\s*,?\s*)+([X"]-){4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # Compress all output labeled with one of the following MIME-types
    # (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
    # and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
    # as `AddOutputFilterByType` is still in the core directives).
    AddOutputFilterByType DEFLATE application/atom+xml \
        application/javascript \
        application/json \
        application/rss+xml \
        application/vnd.ms-fontobject \
        application/x-font-ttf \
        application/x-web-app-manifest+json \
        application/xhtml+xml \
        application/xml \
        font/opentype \
        image/svg+xml \
        image/x-icon \
        text/css \
        text/html \
        text/plain \
        text/x-component \
        text/xml

```

</IfModule>