

```
# Allow access if Flarum is installed in a subdirectory,  
# but another .htaccess in a higher directory denies access.
```

```
<IfModule mod_authz_core.c>
```

```
    Require all granted
```

```
</IfModule>
```

```
<IfModule !mod_authz_core.c>
```

```
    Order Allow,Deny
```

```
    Allow from all
```

```
</IfModule>
```

```
# Fix for https://httpoxy.org vulnerability
```

```
Header unset Proxy
```

```
<IfModule mod_rewrite.c>
```

```
    RewriteEngine on
```

```
    RewriteRule .* - [E=HTTP_AUTHORIZATION:%{HTTP:Authorization}]
```

```
    RewriteRule ^vendor/(.*)?$ / [F,L]
```

```
    RewriteRule ^storage/(.*)?$ / [F,L]
```

```
    RewriteRule ^config.php$ / [F,L]
```

```
    RewriteRule ^.git/(.*)?$ / [F,L]
```

```
    RewriteRule ^api/(.*)$ api.php [QSA,L]
```

```
    RewriteRule ^admin/(.*)$ admin.php [QSA,L]
```

```
    RewriteCond %{REQUEST_FILENAME} !-f
```

```
    RewriteCond %{REQUEST_FILENAME} !-d
```

```
    RewriteRule !^assets/index.php [QSA,L]
```

```
# MultiViews can mess up our rewriting scheme
```

```
Options -MultiViews
```

```
# Autoindex will list all assets files which is not so good
```

```
Options -Indexes
```

```
</IfModule>
```

```
<IfModule mod_deflate.c>
```

```
# Compress all output labeled with one of the following MIME-types
```

```
<#MIME-types and charset>
```

```
<!IfModule mod_filter.c>
```

```
    AddOutputFilterByType DEFLATE application/atom+xml \
                                application/javascript \
                                application/json \
                                application/vnd.ms-fontobject \
                                application/x-font-ttf \
                                application/x-web-app-manifest+json \
                                application/xhtml+xml \
                                application/xml \
                                font/opentype \
                                image/svg+xml \
                                image/x-icon \
                                text/css \
                                text/html \
                                text/plain \
                                text/xml
```

```
</IfModule>
```

```
</IfModule>
```

```
# Configure cache expiry for different file types
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
```

```
ExpiresDefault "access plus 1 second"
```

```
ExpiresByType text/css "access plus 1 year"
```

```
ExpiresByType application/json "access plus 0 seconds"
```

```
ExpiresByType application/xml "access plus 0 seconds"
```

```
ExpiresByType text/xml "access plus 0 seconds"
```

```
ExpiresByType image/x-icon "access plus 1 week"
```

```
ExpiresByType text/html "access plus 0 seconds"
```

```
ExpiresByType application/javascript "access plus 1 year"
```

```
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
```

```
ExpiresByType text/cache-manifest "access plus 0 seconds"
```

```
ExpiresByType image/gif "access plus 1 month"
```

```
ExpiresByType image/jpeg "access plus 1 month"
```

```
ExpiresByType image/png "access plus 1 month"
```

```
ExpiresByType application/atom+xml "access plus 1 hour"
```

```
ExpiresByType application/rss+xml "access plus 1 hour"
```

```
ExpiresByType application/font-woff2 "access plus 1 month"
```

```
ExpiresByType application/font-woff "access plus 1 month"
```

```
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
```

```
ExpiresByType application/atom+xml "access plus 1 hour"
```

```
ExpiresByType application/x-font-ttf           "access plus 1 month"
ExpiresByType font/opentype                   "access plus 1 month"
ExpiresByType image/svg+xml                  "access plus 1 month"
</IfModule>
```