

```

# In case you want to add a .htpasswd authentication
# you'll have to add the host of the shop as an allowed entity,
# so that calls from the host skip the authentication
# Example:
# Order Deny, Allow
# Deny from All
# AuthType Basic
# AuthName "Access not allowed"
# AuthUserFile path_to_htpasswd_file/.htpasswd
# Require valid-user
# Allow from localhost
# Satisfy Any

<IfModule mod_rewrite.c>
Options +FollowSymLinks
RewriteEngine On
RewriteBase /
RewriteRule ^ua/(.*)$ $1

RewriteCond %{REQUEST_URI} config\.inc\.php [NC]
RewriteRule ^config\.inc\.php index\.php [R=301,L]

RewriteCond %{QUERY_STRING} fnc=(getShopVersion|getShopEdition|getRevision) [NC]
RewriteRule ^(.*)$ $1? [R=301,L]

RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK)
RewriteRule .* - [F]

RewriteCond %{REQUEST_URI} oxseo\.php$
RewriteCond %{QUERY_STRING} mod_rewrite_module_is=off
RewriteRule oxseo\.php$ oxseo\.php?mod_rewrite_module_is=on [L]

RewriteCond %{REQUEST_URI} !
(\.admin\/|.core\/|.application\/|.export\/|.modules\/|.out\/|.setup\/|.tmp\/|.views)
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule !(\.html|\/|.jpg|\.css|\.pdf|\.doc|\.gif|\.png|\.js|\.htcl|\.svg)$ %{REQUEST_URI}
[R=301,L]

RewriteCond %{REQUEST_URI} !

```

```
<\/admin\/core\/application\/export\/modules\/out\/setup\/tmp\/views  
RewriteCond %{REQUEST_FILENAME} !-f  
RewriteCond %{REQUEST_FILENAME} !-d  
RewriteRule (\.html\/)$ oxseo.php  
  
RewriteCond %{REQUEST_URI} (\/out\/pictures\/)  
RewriteCond %{REQUEST_FILENAME} !-f  
RewriteCond %{REQUEST_FILENAME} !-d  
RewriteRule (\.jpe?g|\.gif|\.png|\.svg)$ getimg.php  
  
<\/IfModule>  
  
# disabling log file access from outside  
<FilesMatch "(EXCEPTION_LOG\/.txt|\.log$|\.tpl$|pkg\/.rev|\.ini|pkg\/.info|\.pem$)">  
order allow,deny  
deny from all  
<\/FilesMatch>  
  
Options -Indexes  
DirectoryIndex index.php index.html
```