

```
#  
# Apache/PHP/Drupal settings:  
#  
  
# Protect files and directories from prying eyes.  
<FilesMatch "\.(engine|incl|info|install|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?|  
|tmp|svn-base)$|^(code-style\.|Entries\. *|Repository|Root|Tag|Template|all-  
wcp|props|entries|format)$">  
    Order allow,deny  
</FilesMatch>  
  
# Restrict cron.php to be run locally only.  
<Files "cron.php">  
    Order Deny,Allow  
    Deny from all  
    Allow from localhost  
    Allow from 204.12.8.227  
    Allow from 204.12.8.228  
</Files>  
  
# Don't show directory listings for URLs which map to a directory.  
Options -Indexes  
  
# Follow symbolic links in this directory.  
Options +FollowSymLinks  
  
# Make Drupal handle any 404 errors.  
ErrorDocument 404 /index.php  
  
# Force simple error message for requests for non-existent favicon.ico.  
<Files favicon.ico>  
    # There is no end quote below, for compatibility with Apache 1.3.  
    ErrorDocument 404 "The requested file favicon.ico was not found."  
</Files>  
  
# Set the default handler.  
DirectoryIndex index.php  
  
# Override PHP settings. More in sites/default/settings.php  
# but the following cannot be changed at runtime.
```

PHP 4, Apache 1.

```
<IfModule mod_php4.c>
    php_value magic_quotes_gpc            0
    php_value register_globals            0
    php_value session.auto_start        0
    php_value mbstring.http_input       pass
    php_value mbstring.http_output      pass
    php_value mbstring.encoding_transl  0
</IfModule>
```

PHP 4, Apache 2.

```
<IfModule sapi_apache2.c>
    php_value magic_quotes_gpc            0
    php_value register_globals            0
    php_value session.auto_start        0
    php_value mbstring.http_input       pass
    php_value mbstring.http_output      pass
    php_value mbstring.encoding_transl  0
</IfModule>
```

PHP 5, Apache 1 and 2.

```
<IfModule mod_php5.c>
    php_value magic_quotes_gpc            0
    php_value register_globals            0
    php_value session.auto_start        0
    php_value mbstring.http_input       pass
    php_value mbstring.http_output      pass
    php_value mbstring.encoding_transl  0
</IfModule>
```

Requires mod_expires to be enabled.

```
<IfModule mod_expires.c>
    # Enable expirations.
    ExpiresActive On

    # Cache all files for 2 weeks after access (A).
    ExpiresDefault A1209600

    # Do not cache dynamically generated pages.
    ExpiresByType text/html A1
```

```
</IfModule>
```

```
# Various rewrite rules.
```

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine on
```

```
# If your site can be accessed both with and without the 'www.' prefix, you  
# can use one of the following settings to redirect users to your preferred  
# URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:  
#
```

```
# To redirect all users to access the site WITH the 'www.' prefix,  
# (http://example.com/... will be redirected to http://www.example.com/...)  
# adapt and uncomment the following:
```

```
#RewriteCond %{HTTP_HOST} ^atlantishomesllc\.com$ [NC]
```

```
#RewriteRule ^(.*)$ http://www.atlantishomesllc.com/$1 [L,R=301]
```

```
#
```

```
# To redirect all users to access the site WITHOUT the 'www.' prefix,  
# (http://www.example.com/... will be redirected to http://example.com/...)  
# uncomment and adapt the following:
```

```
# RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]
```

```
# RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]
```

```
# Modify the RewriteBase if you are using Drupal in a subdirectory or in a  
# VirtualDocumentRoot and the rewrite rules are not working properly.  
# For example if your site is at http://example.com/drupal uncomment and  
# modify the following line:
```

```
# RewriteBase /drupal
```

```
#
```

```
# If your site is running in a VirtualDocumentRoot at http://example.com/,  
# uncomment the following line:
```

```
# RewriteBase /
```

```
# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_URI} !=/favicon.ico
```

```
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
```

```
</IfModule>
```

```
# $Id: .htaccess,v 1.90.2.3 2008/12/10 20:04:08 goba Exp $
```