

```

#
# Apache/PHP/Drupal settings:
#

# Protect files and directories from prying eyes.
<FilesMatch "\.(engine|incl|info|install|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?|
|tmp|svn-base)$|^(\code-style|.pl|Entries.*|Repository|Root|Tag|Template|all-
wcpops|entries|format)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found."
</Files>

# Set the default handler.
DirectoryIndex index.php

# Override PHP settings. More in sites/default/settings.php
# but the following cannot be changed at runtime.

# PHP 4, Apache 1.
<IfModule mod_php4.c>
    php_value magic_quotes_gpc            0
    php_value register_globals            0
    php_value session.auto_start          0
    php_value mbstring.http_input          pass
    php_value mbstring.http_output          pass
    php_value mbstring.encoding_translation 0
</IfModule>

```

```
</IfModule>
```

```
# PHP 4, Apache 2.
```

```
<IfModule sapi_apache2.c>
```

```
php_value magic_quotes_gpc      0
php_value register_globals      0
php_value session.auto_start    0
php_value mbstring.http_input   pass
php_value mbstring.http_output  pass
php_value mbstring.encoding_translation 0
```

```
</IfModule>
```

```
# PHP 5, Apache 1 and 2.
```

```
<IfModule mod_php5.c>
```

```
php_value magic_quotes_gpc      0
php_value register_globals      0
php_value session.auto_start    0
php_value mbstring.http_input   pass
php_value mbstring.http_output  pass
php_value mbstring.encoding_translation 0
```

```
</IfModule>
```

```
# Requires mod_expires to be enabled.
```

```
<IfModule mod_expires.c>
```

```
# Enable expirations.
```

```
ExpiresActive On
```

```
# Cache all files for 2 weeks after access (A).
```

```
ExpiresDefault A1209600
```

```
# Do not cache dynamically generated pages.
```

```
ExpiresByType text/html A1
```

```
</IfModule>
```

```
# Various rewrite rules.
```

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine on
```

```
# If your site can be accessed both with and without the 'www.' prefix, you
```

```
# can use one of the following settings to redirect users to your preferred
```

```
# URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
```

```
..
```

```
#
# To redirect all users to access the site WITH the 'www.' prefix,
# (http://example.com/... will be redirected to http://www.example.com/...)
# adapt and uncomment the following:
RewriteCond %{HTTP_HOST} ^findingmyphbalance\.com$ [NC]
RewriteRule ^(.*)$ http://www.findingmyphbalance.com/$1 [L,R=301]
#
# To redirect all users to access the site WITHOUT the 'www.' prefix,
# (http://www.example.com/... will be redirected to http://example.com/...)
# uncomment and adapt the following:
# RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]
# RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]

# Modify the RewriteBase if you are using Drupal in a subdirectory or in a
# VirtualDocumentRoot and the rewrite rules are not working properly.
# For example if your site is at http://example.com/drupal uncomment and
# modify the following line:
# RewriteBase /
#
# If your site is running in a VirtualDocumentRoot at http://example.com/,
# uncomment the following line:
RewriteBase /

# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} !=/favicon.ico
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
</IfModule>

# $Id: .htaccess,v 1.90.2.3 2008/12/10 20:04:08 goba Exp $
```