

```

# Protect files and directories from prying eyes.
<FilesMatch "\.(data|include|themes|language|modules)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Customized error messages.
ErrorDocument 404 /index.php

# Set the default handler.
DirectoryIndex index.php

# PHP 4, Apache 1.
<IfModule mod_php4.c>
    php_value magic_quotes_gpc 0
    php_value register_globals 0
    php_value session.auto_start 0
    php_value mbstring.http_input pass
    php_value mbstring.http_output pass
    php_value mbstring.encoding_translation 0
</IfModule>

# PHP 4, Apache 2.
<IfModule sapi_apache2.c>
    php_value magic_quotes_gpc 0
    php_value register_globals 0
    php_value session.auto_start 0
    php_value mbstring.http_input pass
    php_value mbstring.http_output pass
    php_value mbstring.encoding_translation 0
</IfModule>

# PHP 5, Apache 1 and 2.
<IfModule mod_php5.c>
    php_value magic_quotes_gpc 0
    php_value register_globals 0

```

```
php_value register_globals 0
php_value session.auto_start 0
php_value mbstring.http_input pass
php_value mbstring.http_output pass
php_value mbstring.encoding_translation 0
</IfModule>
```

```
# Requires mod_expires to be enabled.
```

```
<IfModule mod_expires.c>
```

```
# Enable expirations.
```

```
ExpiresActive On
```

```
# Cache all files for 2 weeks after access (A).
```

```
ExpiresDefault A1209600
```

```
# Do not cache dynamically generated pages.
```

```
ExpiresByType text/html A1
```

```
</IfModule>
```

```
# Rewrite rule.
```

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine on
```

```
# Needed for NetworkSolutions and maybe other hosting providers
```

```
# RewriteBase /
```

```
# Rewrite URLs of the form 'index.php?p=x'.
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule ^(.*)$ index.php?p=$1 [L,QSA]
```

```
</IfModule>
```