

```
#
#   PHP include_path to Trax config directory
#   $Id: .htaccess 199 2006-05-05 01:52:43Z haas $
#
php_value include_path ../home/username/trax/config

# Redirect all requests not available on the filesystem to Trax
RewriteEngine On

# If you don't want Trax to look in certain directories,
# use the following rewrite rules so that Apache won't rewrite certain requests
#
# Example:
# RewriteCond %{REQUEST_URI} ^/nottrax.*
# RewriteRule .* - [L]

# If your Trax application is accessed via an Alias directive,
# then you MUST also set the RewriteBase in this htaccess file.
#
# Example:
# Alias /mytraxapp /path/to/mytraxapp/public
# RewriteBase /mytraxapp

RewriteRule ^$ index.html [QSA]
RewriteRule ^([\^.]*)$ $1.html [QSA]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond $1 !-d
RewriteRule ^(\.*)$ /dispatch.php?$1 [QSA,L]

# In case Trax experiences terminal errors
# Instead of displaying this message you can supply
# a file here which will be rendered instead
#
# Example:
# ErrorDocument 500 /500.html

ErrorDocument 500 "<h2>Application error</h2>Trax application failed to start properly"
```