

```
RewriteEngine On
```

```
# cache files
```

```
<ifmodule mod_expires.c>
```

```
<Filesmatch "\.(j|p)g(j|e)|png|gif|j|s|css|ico|woff|ttf|svg|eot)$">
```

```
ExpiresActive on
```

```
ExpiresDefault "access plus 7 days"
```

```
</Filesmatch>
```

```
</ifmodule>
```

```
# The following rule tells Apache that if the requested filename  
# exists, simply serve it.
```

```
RewriteCond %{REQUEST_FILENAME} -s [OR]
```

```
RewriteCond %{REQUEST_FILENAME} -l [OR]
```

```
RewriteCond %{REQUEST_FILENAME} -d
```

```
RewriteRule ^.*$ - [NC,L]
```

```
# The following rewrites all other queries to index.php. The  
# condition ensures that if you are using Apache aliases to do  
# mass virtual hosting, the base path will be prepended to  
# allow proper resolution of the index.php file; it will work  
# in non-aliased environments as well, providing a safe, one-size  
# fits all solution.
```

```
RewriteCond %{REQUEST_URI}::$1 ^(/.+)(.+)$::\2$
```

```
RewriteRule ^(.*) - [E=BASE:%1]
```

```
RewriteRule ^(.*)$ %{ENV:BASE}index.php [NC,L]
```