

Options +FollowSymLinks

```
# Most of this is taken from h5bp examples here...
# https://github.com/h5bp/server-configs-apache/blob/master/dist/.htaccess

# Redirect to HTTPS
<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /

# RewriteCond %{HTTPS} !=on
# RewriteRule ^(.*)$ https://%{HTTP_HOST}/$1 [R=301,L]
</IfModule>

# Strip www from url for consistency and SEO concerns.
<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteCond %{HTTPS} !=on
    RewriteCond %{HTTP_HOST} ^www\.(.+) [NC]
    RewriteRule ^ %ENV:PROTO://%1%{REQUEST_URI} [R=301,L]
</IfModule>

#=====
# Wordpress Pretty URLs
# RewriteRule ^index\.php$ - [L]

# RewriteCond %{REQUEST_FILENAME} !-f
# RewriteCond %{REQUEST_FILENAME} !-d
# RewriteRule . /index.php [L]
#=====

<IfModule mod_php5.c>

#=====
# Override some PHP defaults

# php_value post_max_size      20M
# php_value upload_max_filesize 20M
# php_value memory_limit       500M
# php_value SMTP                localhost
# php_value smtp_auth           on
```

```
# php_value smtp_port 25
# php_value sendmail_from mail@example.com
#=====

# Send mail to catchmail for development
# (Find catchmail path with `which catchmail`)
# http://berk.es/2011/05/29/mailcatcher-for-drupal-and-other-php-applications-the-simple-
version
# php_value sendmail_path /usr/bin/env /Users/jasonpolette/.rvm/gems/ruby-1.9.3-
p194@global/bin/catchmail
```

```
</IfModule>
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
```

```
ExpiresByType image/x-icon "access plus 1 month"
```

```
ExpiresByType image/ico "access plus 1 month"
```

```
ExpiresByType image/jpg "access plus 1 month"
```

```
ExpiresByType image/jpg "access plus 1 month"
```

```
ExpiresByType image/jpeg "access plus 1 month"
```

```
ExpiresByType image/gif "access plus 1 month"
```

```
ExpiresByType image/png "access plus 1 month"
```

```
ExpiresByType image/svg+xml "access plus 1 month"
```

```
ExpiresByType application/javascript "access plus 1 day"
```

```
ExpiresByType text/css "access plus 1 day"
```

```
</IfModule>
```

```
<IfModule mod_filter.c>
```

```
    AddOutputFilterByType DEFLATE "application/atom+xml" \
                                "application/javascript" \
                                "application/json" \
                                "application/ld+json" \
                                "application/manifest+json" \
                                "application/rdf+xml" \
                                "application/rss+xml" \
                                "application/schema+json" \
                                "application/vnd.geo+json" \
                                "application/vnd.ms-fontobject" \
                                "application/x-font-ttf" \
                                "application/x-javascript" \
                                "application/x-web-app-manifest+json" \
                                "text/css" \
                                "text/javascript" \
                                "text/plain" \
                                "text/xml"
```

```
"application/xhtml+xml" \  
"application/xml" \  
"font/eot" \  
"font/opentype" \  
"image/bmp" \  
"image/svg+xml" \  
"image/vnd.microsoft.icon" \  
"image/x-icon" \  
"text/cache-manifest" \  
"text/css" \  
"text/html" \  
"text/javascript" \  
"text/plain" \  
"text/vcard" \  
"text/vnd.rim.location.xloc" \  
"text/vtt" \  
"text/x-component" \  
"text/x-cross-domain-policy" \  
"text/xml"
```

</IfModule>