

```

# magically, us .htaccess file
# Author:      Kevin Richardson <kevin@magically.us>
# Last updated: 19-Jun-2011 2:45pm EST
# ---
# Many thanks to HTML5 Boilerplate Mobile for the tips and tricks.

# -----
# Enable access from all domains for webfonts.
# -----
<FilesMatch "\.(ttf|otf|eot|woff|font. css)$">
  <IfModule mod_headers.c>
    Header set Access-Control-Allow-Origin "*"
  </IfModule>
</FilesMatch>

# -----
# Proper MIME types.
# -----
# audio
AddType audio/ogg                oga ogg

# video
AddType video/ogg                ogv
AddType video/mp4                mp4
AddType video/webm               webm

# Proper svg serving. Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml           svg svgz
AddEncoding gzip                 svgz

# webfonts
AddType application/vnd.ms-fontobject eot
AddType font/truetype            ttf
AddType font/opentype            otf
AddType application/x-font-woff   woff

# assorted types
AddType image/x-icon             ico
AddType image/webp               webp
AddType font/woff                woff

```

```

AddType text/cache-manifest appcache manifest
AddType text/x-component htc
AddType application/x-chrome-extension crx
AddType application/x-xpinstall xpi
AddType application/octet-stream safariextz

# -----
# gzip compression
# -----

<IfModule mod_deflate.c>

# force deflate for mangled headers developer.yahoo.com/blogs/ym/post/2010/12/pushing-
beyond-gzipping/
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
    ^((gzip|deflate)\s,?\s(gzip|deflate)?|X(4,13)|^(4,13)|-(4,13))$ HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
  </IfModule>
</IfModule>
# html, txt, css, js, json, xml, htc:
<IfModule filter_module>
  FilterDeclare COMPRESS
  FilterProvider COMPRESS DEFLATE resp=Content-Type
  /text/(html|css|javascript|plain|xml|-component)/
  FilterProvider COMPRESS DEFLATE resp=Content-Type /application/(javascript|json|xml|x-
  javascript)/
  FilterChain COMPRESS
  FilterProtocol COMPRESS change=yes;byteranges=no
</IfModule>

<IfModule !mod_filter.c>
  # Legacy versions of Apache
  AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
  AddOutputFilterByType DEFLATE text/javascript application/javascript application/x-
  javascript
  AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
</IfModule>

# webfonts and svg:

```

```

<FilesMatch "\.(ttf|otf|eot|svg)$" >
  SetOutputFilter DEFLATE
</FilesMatch>
</IfModule>

# -----
# Expires headers (for better cache control)
# -----

# these are pretty far-future expires headers
# they assume you control versioning with cachebusting query params like
# <script src="application.js?20100608">
# additionally, consider that outdated proxies may miscache
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/

# if you don't use filenames to version, lower the css and js to something like
# "access plus 1 week" or so

<IfModule mod_expires.c>
  ExpiresActive on

# Perhaps better to whitelist expires rules? Perhaps.
  ExpiresDefault                               "access plus 1 month"

# cache.appcache needs re-requests in FF 3.6 (thx Remy "Introducing HTML5")
  ExpiresByType text/cache-manifest           "access plus 0 seconds"

# your document html
  ExpiresByType text/html                       "access plus 0 seconds"

# data
  ExpiresByType text/xml                        "access plus 0 seconds"
  ExpiresByType application/xml                "access plus 0 seconds"
  ExpiresByType application/json              "access plus 0 seconds"

# rss feed
  ExpiresByType application/rss+xml            "access plus 1 hour"

# favicon (cannot be renamed)
  ExpiresByType image/x-icon                   "access plus 1 week"

```

```
# media: images, video, audio
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/jpg "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# htc files (css3pie)
ExpiresByType text/x-component "access plus 1 month"

# webfonts
ExpiresByType font/truetype "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# css and javascript
ExpiresByType text/css "access plus 1 week"
ExpiresByType application/javascript "access plus 1 week"
ExpiresByType text/javascript "access plus 1 week"

<IfModule mod_headers.c>
  Header append Cache-Control "public"
</IfModule>

</IfModule>

# -----
# ETag removal
# -----

# Since we're sending far-future expires, we don't need ETags for
# static content.
# developer.yahoo.com/performance/rules.html#etags
FileETag None

# -----
```

```
# Enable the Rewrite module for the following options.
# -----
RewriteEngine On

# -----
# Rewrite www.domain.com -> domain.com
# -----
<IfModule mod_rewrite.c>
    RewriteCond %{HTTPS} !=on
    RewriteCond %{HTTP_HOST} ^www\.(.+)$ [NC]
    RewriteRule ^(.*)$ http://%1/$1 [R=301,L]
</IfModule>

# -----
# Filename-based cache busting: Redirect something like
# /css/style.2011-06-05.css -> /css/style.css
# -----
<IfModule mod_rewrite.c>
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteRule ^(.+)\.(\d+)\.(js|css|png|jpg|gif|apache)$ $1.$3 [L]
</IfModule>

# -----
# Rewrite URIs that do not match files on the disk to index.php.
# -----
<IfModule mod_rewrite.c>
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteRule . index.php [L]
</IfModule>

# -----
# UTF-8 encoding
# -----
# use utf-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# force utf-8 for a number of file formats
AddCharset utf-8 .html .css .js .xml .json .rss
```

```
# -----  
# Various security options.  
# -----  
# Block access to "hidden" directories whose names begin with a period. This  
# includes directories used by version control systems such as Subversion or Git.  
<IfModule mod_rewrite.c>  
    RewriteRule "(^/)\." - [F]  
</IfModule>
```