

```
##
# @file      AblePolecat-View/usr/share/local/.htaccess
# @brief     Example Apache host access settings.
#
# @author    Karl Kuhrman
# @copyright 2015 [GPL V2] Karl Kuhrman
#
#
# Set the default handler.
#
DirectoryIndex index.php
#
# Override default Apache handlers.
#
Options -Indexes
Options +FollowSymLinks
Options +MultiViews

<IfModule mod_rewrite.c>
    RewriteEngine on

    #
    # Block access to "hidden" directories whose names begin with a period.
    # (This rule exists mainly to prevent access to Git files).
    #
    RewriteRule "(^|/)\." - [F]

    #
    # If using an alias to access the site (e.g. http://localhost/polecat),
    # define the base below relative to the server document root.
    # (e.g. RewriteBase /polecat)
    #
    RewriteBase /AblePolecat-View

    #
    # Pass all requests not referring directly to files in the file system to
    # index.php.
    #
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteRule ^.*$ index.php [L]
```

```
RewriteCond %{REQUEST_FILENAME} !\.(.*)(.js|.ico|.gif|.jpg|.png|.css|.eot|.ttf|.woff|.ttm)|$  
RewriteCond %{REQUEST_FILENAME} !-f  
RewriteCond %{REQUEST_FILENAME} !-d  
RewriteCond %{REQUEST_URI} !=/favicon.ico  
RewriteRule ^ index.php [L]  
</IfModule>
```