

```
RewriteEngine On
```

```
RewriteRule ^code(/)?$ code.php
```

```
RewriteRule ^login/$ loginprocess.php
```

```
RewriteRule ^logout/$ logoutprocess.php
```

```
RewriteRule ^register/$ registration.php
```

```
RewriteRule ^cloud-save/$ saveimage.php
```

```
RewriteRule ^cloud-delete/$ deleteimage.php
```

```
RewriteCond %{QUERY_STRING} ^user_id=(\d+)$
```

```
RewriteRule ^cloud-images/$ getimages.php?user_id=%1
```

```
#####
```

```
Options -MultiViews
```

```
Options -Indexes
```

```
# Force the latest IE version, in various cases when it may fall back to IE7 mode
```

```
# github.com/rails/rails/commit/123eb25#commitcomment-118920
```

```
# Use ChromeFrame if it's installed for a better experience for the poor IE folk
```

```
<IfModule mod_setenvif.c>
```

```
  <IfModule mod_headers.c>
```

```
    BrowserMatch MSIE ie
```

```
    Header set X-UA-Compatible "IE=Edge,chrome=1" env=ie
```

```
  </IfModule>
```

```
</IfModule>
```

```
<IfModule mod_headers.c>
```

```
# Because X-UA-Compatible isn't sent to non-IE (to save header bytes),
```

```
# We need to inform proxies that content changes based on UA
```

```
  Header append Vary User-Agent
```

```
# Cache control is set only if mod_headers is enabled, so that's unnecessary to declare
```

```
</IfModule>
```

```
# video
```

```
AddType video/ogg ogg
```

```
AddType video/ogg ogv
```

```
AddType video/mp4 mp4
```

```
AddType video/webm webm
```

```

# Proper svg serving. Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml          svg svgz
AddEncoding gzip                svgz

# webfonts
AddType application/vnd.ms-fontobject eot
AddType font/truetype             ttf
AddType font/opentype             otf
AddType font/woff                 woff

# assorted types
AddType image/vnd.microsoft.icon  ico
AddType image/webp                 webp
AddType text/cache-manifest        manifest
AddType text/x-component           htc
AddType application/x-chrome-extension crx

# gzip compression.
<IfModule mod_deflate.c>

# html, txt, css, js, json, xml, htc:
  AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
  AddOutputFilterByType DEFLATE text/javascript application/javascript application/x-
javascript
  AddOutputFilterByType DEFLATE text/xml application/xml text/x-component

# webfonts and svg:
  <FilesMatch "\.(ttf|otf|eot|svg)$" >
    SetOutputFilter DEFLATE
  </FilesMatch>
</IfModule>

# disable gzip compression for video files
SetEnvIfNoCase Request_URI \.(og[gv]|mp4|m4v|webm)$ no-gzip dont-vary

# these are pretty far-future expires headers
# they assume you control versioning with cachebusting query params like
# <script src="application.js?20100608">
# additionally, consider that outdated proxies may miscache
# "Expires: Wed, 11 Jun 2008 12:00:00 GMT"

```

```
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/

# if you don't use filenames to version, lower the css and js to something like
# "access plus 1 week" or so
<IfModule mod_headers.c>

    # cache.manifest needs re-requests in FF 3.6 (thx Remy "Introducing HTML5")
    <FilesMatch "\.(manifest)$">
        Header set Expires "access plus 0 seconds"
    </FilesMatch>

    # media: images, video, audio
    <FilesMatch "\.(jpg|jpeg|png|gif|swf|ogg|ogv|mp4|mp3|webm)$">
        Header set Expires "access plus 1 month"
    </FilesMatch>

    # webfonts
    <FilesMatch "\.(ttf|otf|woff|svg|svgz|eot)$">
        Header set Expires "access plus 1 month"
    </FilesMatch>

    # css and javascript
    <FilesMatch "\.(css|js)$">
        Header set Expires "access plus 1 month"
    </FilesMatch>

    Header append Cache-Control "public"

</IfModule>

# Since we're sending far-future expires, we don't need ETags for
# static content.
# developer.yahoo.com/performance/rules.html#etags
FileETag None

# you probably want www.example.com to forward to example.com -- shorter URLs are sexier.
# no-www.org/faq.php?q=class\_b
<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteCond %{HTTPS} !=on
    RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
```

```
RewriteRule ^(.*)$ http://%1/$1 [R=301,L]  
</IfModule>
```

```
# use utf-8 encoding for anything served text/plain or text/html
```

```
AddDefaultCharset utf-8
```

```
# force utf-8 for a number of file formats
```

```
AddCharset utf-8 .html .css .js .xml .json .rss
```

```
# We don't need to tell everyone we're apache.
```

```
ServerSignature Off
```