

```
# eine kleine erweiterung der wordpress eigenen htaccess
# nicht multi-site-kompatibel - dafür muss der block "# BEGIN WordPress" angepasst werden
# v1.0.0
```

Basics

```
Options +FollowSymlinks -Indexes
FileETag none
Header set Connection keep-alive
AddType x-font/woff .woff
```

```
<IfModule mod_rewrite.c>
```

```
    RewriteEngine On
    RewriteBase /
```

403 Block bad requests

```
RewriteRule ^admin/ - [F,L]
RewriteRule ^admin.php - [F,L]
RewriteRule ^administrator?/ - [F,L]
RewriteRule main.jsp - [F,L]
RewriteRule main.aspx - [F,L]
RewriteRule main.html - [F,L]
RewriteRule main.php - [F,L]
RewriteRule main.asp - [F,L]
RewriteRule main.htm - [F,L]
RewriteRule contact.asp - [F,L]
RewriteRule contact.aspx - [F,L]
RewriteRule contact.htm - [F,L]
RewriteRule contact.html - [F,L]
RewriteRule contact.php - [F,L]
RewriteRule timthumb.php - [F,L]
RewriteRule GetFoldersAndFiles - [F,L]
RewriteRule fckeditor - [F,L]
RewriteRule FCKeditor - [F,L]
RewriteRule filemanager - [F,L]
RewriteRule open-flash-charts - [F,L]
RewriteRule ofc_upload_image.php - [F,L]
RewriteRule hatz.php - [F,L]
RewriteRule uploadify.php - [F,L]
RewriteRule info.php - [F,L]
RewriteRule register - [F,L]
RewriteRule - [F,L]
```

```

RewriteRule .ntaccess - [F,L]
RewriteRule .htpasswd - [F,L]
RewriteRule ._error.log - [F,L]
RewriteRule wp-config.php - [F,L]
RewriteRule liesmich.html - [F,L]
RewriteRule readme.html - [F,L]
RewriteRule license.txt - [F,L]
RewriteRule error.log - [F,L]
RewriteRule readme.txt - [F,L]
RewriteRule readme.md - [F,L]
</IfModule>

<IfModule mod_rewrite.c>
    # reenable to export blog
    RewriteEngine On
    RewriteCond %{QUERY_STRING} author=(.*)
    RewriteRule ^(.*) - [F]
</IfModule>

<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteCond %{QUERY_STRING} twitterpage(.*)
    RewriteRule ^(.*) - [G]
</IfModule>

# block some crawlers
<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteCond %{HTTP_USER_AGENT} ^.*(
crawler4j|HTTrack|Yandex|Baidu|MegaIndex|libwww|AdvBot|RU_Bot).*$ [NC]
    RewriteRule .* - [F,L]
</IfModule>

# block WPscan crawlers
#<IfModule mod_rewrite.c>
# RewriteEngine On
# RewriteCond %{HTTP_USER_AGENT} ^.*(WPScan).*$ [NC]
# RewriteRule .* - [F,L]
#</IfModule>

# Block comments via Crossposting
<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteCond %{QUERY_STRING} .*comment.*
    RewriteRule ^(.*) - [F]
</IfModule>

```

```
RewriteEngine On
RewriteBase /
RewriteCond %{REQUEST_METHOD} POST
RewriteCond %{REQUEST_URI} .wp-comments-post\.php*
RewriteCond %{HTTP_REFERER} !.*${SERVER_NAME}.* [OR]
RewriteCond %{HTTP_USER_AGENT} ^$
RewriteRule (.*) ^http://%{REMOTE_ADDR}/$ [R=301,L]
</IfModule>

# Block the include-only files.
<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteBase /
    RewriteRule ^wp-admin/includes/ - [F,L]
    RewriteRule !^wp-includes/ - [S=3]
    RewriteRule ^wp-includes/[^/]+\.\php$ - [F,L]
    RewriteRule ^wp-includes/js/tinymce/langs/.+\.\php - [F,L]
    RewriteRule ^wp-includes/theme-compat/ - [F,L]
    RewriteRule ^wp-content/uploads/[^/]+\.\php$ - [F,L]
    RewriteRule ^(.+)/wp-login.php - [F,L]
</IfModule>

<IfModule mod_expires.c>
    ExpiresActive On

    ExpiresDefault "access plus 1 month"
    ExpiresByType image/x-icon "access plus 1 year"
    ExpiresByType image/gif "access plus 1 month"
    ExpiresByType image/png "access plus 1 month"
    ExpiresByType image/jpg "access plus 1 month"
    ExpiresByType image/jpeg "access plus 1 month"
    ExpiresByType text/css "access plus 1 month"
    ExpiresByType application/javascript "access plus 1 year"
    ExpiresByType x-font/woff "access plus 1 year"
    ExpiresByType video/webm "access plus 1 year"
</IfModule>

<IfModule mod_deflate.c>
    # Compress HTML, CSS, JavaScript, Text, XML and fonts
    AddOutputFilterByType DEFLATE application/javascript
    AddOutputFilterByType DEFLATE application/rss+xml
```

```
AddOutputFilterByType DEFLATE application/vnd.ms-fontobject
AddOutputFilterByType DEFLATE application/x-font
AddOutputFilterByType DEFLATE application/x-font-opentype
AddOutputFilterByType DEFLATE application/x-font-otf
AddOutputFilterByType DEFLATE application/x-font-truetype
AddOutputFilterByType DEFLATE application/x-font-ttf
AddOutputFilterByType DEFLATE application/x-font-woff
AddOutputFilterByType DEFLATE application/x-javascript
AddOutputFilterByType DEFLATE application/xhtml+xml
AddOutputFilterByType DEFLATE application/xml
AddOutputFilterByType DEFLATE font/opentype
AddOutputFilterByType DEFLATE font/otf
AddOutputFilterByType DEFLATE font/ttf
AddOutputFilterByType DEFLATE image/svg+xml
AddOutputFilterByType DEFLATE image/x-icon
AddOutputFilterByType DEFLATE image/png
AddOutputFilterByType DEFLATE image/jpeg
AddOutputFilterByType DEFLATE text/css
AddOutputFilterByType DEFLATE text/html
AddOutputFilterByType DEFLATE text/javascript
AddOutputFilterByType DEFLATE text/plain
AddOutputFilterByType DEFLATE text/xml
```

```
# Remove browser bugs (only needed for really old browsers)
```

```
BrowserMatch ^Mozilla/4 gzip-only-text/html
BrowserMatch ^Mozilla/4\.0[678] no-gzip
BrowserMatch \bMSIE !no-gzip !gzip-only-text/html
Header append Vary User-Agent
```

```
</IfModule>
```

```
<FilesMatch "\.(txt|log|xml|css|js|gz|md)$">
```

```
Header set X-Robots-Tag "noindex"
```

```
</FilesMatch>
```

```
# BEGIN WordPress
```

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine On
```

```
RewriteBase /
```

```
RewriteRule ^index\.php$ - [L]
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule . /index.php [L]
```

```
</IfModule>
```

```
# END WordPress
```