

```
# $Id$  
  
# Password protection settings  
AuthName "Restricted Area"  
AuthType Basic  
AuthUserFile /var/www/org/example/.htpasswd  
AuthGroupFile /dev/null  
  
# Enable content negotiation  
Options +MultiViews  
  
# MIME type negotiation setup  
AddType application/xhtml+xml .xhtml  
AddType text/html; q=0.7 .html  
DirectoryIndex index  
  
### Language negotiation setup  
  
# Available languages  
AddLanguage en .en  
AddLanguage fr .fr  
  
# Priority (highest first)  
LanguagePriority en fr  
  
# Fallback to specified language priority if the browser doesn't supply any of the  
# supported languages  
ForceLanguagePriority Fallback  
  
RewriteEngine On  
RewriteBase /  
  
# Set the language from the URL parameter  
RewriteCond %{QUERY_STRING} ^(?:.*&)language=(en|fr).*$  
RewriteRule ^ - [env=prefer-language:%1]  
  
# Set folder of custom php.ini  
suPHP_ConfigPath /var/www/org/example/  
  
# Password protect PHP info  
#
```

```
<Files ~ppinno.php*>
    require valid-user
</Files>

# Hide .htaccess and .htpasswd
<FilesMatch "\.ht\.(?!conf)$">
    Order allow,deny
    Deny from all
</FilesMatch>

# Hide error log
<Files error.log>
    Order allow,deny
    Deny from all
</Files>

# vCard MIME type + encoding must be forced for some reason
<Files *.vcf>
    ForceType 'text/x-vcard; charset=ISO-8859-1'
</Files>
```