

```
# Allow webfonts from different (sub)domains
# (For example Typekit)
<FilesMatch "\.(ttf|ttc|otf|eot|woff)$">
  <IfModule mod_headers.c>
    Header set Access-Control-Allow-Origin "*"
  </IfModule>
</FilesMatch>
```

RewriteEngine On

```
# Force www
# - Exclude urls starting with localhost
# - Check whether the Host value is not empty (in case of HTTP/1.0)
# - Check for 2 dots or not (instead of checking for www, because that would break
subdomains)
# - Checks for HTTPS (%{HTTPS} is either on or off, so %{HTTPS}s is either on or off and
in case of on the s is matched)
# - The substitution part of RewriteRule then just merges the information parts to a full
URL
RewriteCond %{HTTP_HOST} !^localhost
RewriteCond %{HTTP_HOST} ^(.*)$ [NC]
RewriteCond %{HTTP_HOST} !^(.*)\.(.*)\. [NC]
RewriteCond %{HTTPS}s ^on(s)|
RewriteRule ^ HTTP%1://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^ index.php [QSA,L]
```