

```
# In case you want to add a .htpasswd authentication
# you'll have to add the host of the shop as an allowed entity,
# so that calls from the host skip the authentication
# Example:
# Order Deny, Allow
# Deny from All
# AuthType Basic
# AuthName "Access not allowed"
# AuthUserFile path_to_htpasswd_file/.htpasswd
# Require valid-user
# Allow from localhost
# Satisfy Any
```

```
<IfModule mod_rewrite.c>
```

```
Options +FollowSymLinks
```

```
RewriteEngine On
```

```
RewriteBase /oxid
```

```
RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK)
```

```
RewriteRule .* - [F]
```

```
RewriteCond %{REQUEST_URI} oxseo\.php$
```

```
RewriteCond %{QUERY_STRING} mod_rewrite_module_is=off
```

```
RewriteRule oxseo\.php$ oxseo.php?mod_rewrite_module_is=on [L]
```

```
RewriteCond %{REQUEST_URI} !
```

```
(\admin\|core\|application\|export\|modules\|out\|setup\|tmp\|views:
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule !(\.html|\.|\.jpg|\.css|\.pdf|\.doc|\.gif|\.png|\.js|\.htc)$ %{REQUEST_URI}/
```

```
[R=301,L]
```

```
RewriteCond %{REQUEST_URI} !
```

```
(\admin\|core\|application\|export\|modules\|out\|setup\|tmp\|views:
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule (\.html|\/)$ oxseo.php
```

```
RewriteCond %{REQUEST_URI} (\out\pictures\|
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule (\.jpe?gl\.gifl\.png)$ getimg.php
```

```
</IfModule>
```

```
# disabling log file access from outside
```

```
<FilesMatch "(EXCEPTION_LOG\.txtl\.log$l\.tpl$l pkg\.revl\.inil pkg\.infol\.pem$)">
```

```
order allow,deny
```

```
deny from all
```

```
</FilesMatch>
```

```
Options -Indexes
```

```
DirectoryIndex index.php index.html
```