

```

# Change YOUR_TOKEN to your prerender token and uncomment that line if you want to cache url
# Change http://example.com (at the end of the last RewriteRule) to your website url

<IfModule mod_headers.c>
    #RequestHeader set X-Prerender-Token "9j25IihuLcbBm7cAAxSs"
</IfModule>

<IfModule mod_rewrite.c>
    RewriteEngine On

    <IfModule mod_proxy_http.c>
        RewriteCond %{HTTP_USER_AGENT} baiduspider|facebookexternalhit|twitterbot [NC,OR]
        RewriteCond %{QUERY_STRING} _escaped_fragment_

        # Only proxy the request to Prerender if it's a request for HTML
        RewriteRule ^(?:.)*?
        (\.js|\.css|\.xml|\.less|\.png|\.jpg|\.jpeg|\.gif|\.pdf|\.doc|\.txt|\.ico|\.rss|\.zip|\.mp3|
        (.*) http://service.prerender.io/http://example.com/$2 [P,L]
    </IfModule>
</IfModule>

# #####
# # WEB PERFORMANCE #
# #####

# -----
# | Compression |
# -----

<IfModule mod_deflate.c>

    # Force compression for mangled headers.
    # http://developer.yahoo.com/blogs/ymdn/posts/2010/12/pushing-beyond-gzipping
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$ ^(gzip|deflate)
            RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # Comment all output labeled with one of the following MIME types

```

```
# Compress all output labeled with one of the following mime-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
# as `AddOutputFilterByType` is still in the core directives).
```

```
<IfModule mod_filter.c>
```

```
    AddOutputFilterByType DEFLATE application/atom+xml \
                                application/javascript \
                                application/json \
                                application/rss+xml \
                                application/vnd.ms-fontobject \
                                application/x-font-ttf \
                                application/x-web-app-manifest+json \
                                application/xhtml+xml \
                                application/xml \
                                font/opentype \
                                image/svg+xml \
                                image/x-icon \
                                text/css \
                                text/html \
                                text/plain \
                                text/x-component \
                                text/xml
```

```
</IfModule>
```

```
</IfModule>
```

```
# -----
# | Content transformations |
# -----
```

```
# Prevent some of the mobile network providers from modifying the content of
# your site: http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.9.5.
```

```
# <IfModule mod_headers.c>
#   Header set Cache-Control "no-transform"
# </IfModule>
```

```
# -----
# | ETag removal |
# -----
```

```
-----
```

```
# Since we're sending far-future expires headers (see below), ETags can
# be removed: http://developer.yahoo.com/performance/rules.html#etags.
```

```
# `FileETag None` is not enough for every server.
```

```
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>
```

FileETag None

```
# -----
# | Expires headers (for better cache control) |
# -----
```

```
# The following expires headers are set pretty far in the future. If you don't
# control versioning with filename-based cache busting, consider lowering the
# cache time for resources like CSS and JS to something like 1 week.
```

```
<IfModule mod_expires.c>

    ExpiresActive on
    ExpiresDefault "access plus 1 month"

    # CSS
    ExpiresByType text/css "access plus 3 days"

    # Data interchange
    ExpiresByType application/json "access plus 0 seconds"
    ExpiresByType application/xml "access plus 0 seconds"
    ExpiresByType text/xml "access plus 0 seconds"

    # Favicon (cannot be renamed!) and cursor images
    ExpiresByType image/x-icon "access plus 1 week"

    # HTML components (HTCs)
    ExpiresByType text/x-component "access plus 1 month"

    # HTML
    ExpiresByType text/html "access plus 0 seconds"

    # JavaScript
```

ExpiresByType application/javascript "access plus 3 days"

Manifest files

ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"

ExpiresByType text/cache-manifest "access plus 0 seconds"

Media

ExpiresByType audio/ogg "access plus 1 month"

ExpiresByType image/gif "access plus 1 month"

ExpiresByType image/jpeg "access plus 1 month"

ExpiresByType image/png "access plus 1 month"

ExpiresByType video/mp4 "access plus 1 month"

ExpiresByType video/ogg "access plus 1 month"

ExpiresByType video/webm "access plus 1 month"

Web feeds

ExpiresByType application/atom+xml "access plus 1 hour"

ExpiresByType application/rss+xml "access plus 1 hour"

Web fonts

ExpiresByType application/font-woff "access plus 3 month"

ExpiresByType application/vnd.ms-fontobject "access plus 3 month"

ExpiresByType application/x-font-ttf "access plus 3 month"

ExpiresByType font/opentype "access plus 3 month"

ExpiresByType image/svg+xml "access plus 3 month"

</IfModule>